

Storage Tanks



Narrow Poly Vertical Tanks

55 to 1500 Gallon

These Polyethylene Tanks have been designed with a narrow diameter for tight places and for use in containment dikes.

DESIGNED FOR PRODUCTS WEIGHING UP TO 14 LBS./GALLON



- Medium & High Density Polyethylene
- Ultraviolet Inhibitor
- Translucent/White
- Gallonage Markers
- Siphon Tube Included on 300 Gallon & Larger Tanks
- 3 Year Warranty

Part No.	Gallons	Diameter	Height	Drain	Fillwell	Wt.
RT VT0055-20	55	20"	47"	1"	5"	23 lbs.
RT VT105	105	23"	65"	1"	7"	40 lbs.
RT VT0135-23	135	23"	82"	1"	16"	47 lbs.
RT VT0135-28	135	28"	59"	1"	8"	47 lbs.
RT VT0175-31	175	31"	61"	1-1/2"	8"	56 lbs.
RT VT0225-31	200	31"	76"	1-1/2"	8"	66 lbs.
RT VT0300-35	300	35"	81"	2"	8"	88 lbs.
RT VT0425-42	425	42"	75"	2"	8"	102 lbs.
RT VT0505-46	505	46"	80"	2"	16"	120 lbs.
RT VT0600-46	600	46"	91"	2"	16"	132 lbs.
RT VT0800-46	800	46"	118"	2"	16"	175 lbs.
RT VT1000-64	1000	64"	81"	2"	16"	252 lbs.
RT VT1500-64	1500	64"	115"	2"	16"	337 lbs.

CALL for CURRENT PRICING



Storage Tanks



TANK FEATURES:

- Maximum Temperature is 140° F.
- Flat spots located on bottom sidewall for additional fitting installation.
- Two top-edge molded-in lugs for sure & safe tie down on 150 Gallon & Larger.
- Heavy-duty polyethylene with ultra-violet inhibitors added for protection against sunlight.
- Built-In Gallonage indicator.
- Standard color is yellow. White Also Available. Shown in some sizes.

Part No.	Capacity	Dia.	Ht.	Fillwell	Fitting Size	Siphon Tube	Wt. Lbs.
RV 41856	* 200 Gallon	30"	72"	8"	2"	Yes	52
RV 47401	* 210 Gallon	32"	67"	16"	2"	No	59
RV 47484	* 300 Gallon	35"	80"	10"	2"	Yes	80
RV 41339	550 Gallon	67"	42"	16"	2"	Yes	105
RV 45218	1550 Gallon	87"	65"	10"	2"	Yes	283

CALL for CURRENT PRICING

Storage Tanks

Rotationally Molder Polyethylene

- Yellow Color is Standard - (White is also available)



- Rectangular "Leg" Tanks
- 5" Fillwell & splash guard on 30 to 100 Gallon. 10" Fillwell & splash guard on 200 & 300 gallon.
- Flat area on each end for fittings or agitation (order fittings separately).
- Attractive compact design requiring no complex saddling or support structures.
- Molded in gallonage indicators on end and sidewall.
- Ribbed for extra strength with U-V inhibitors added for protection against sunlight.
- Outlet fittings must be ordered separately.
- 300 Gallon tank is standard with baffle.
- Ultra-Violet Inhibitors.

Part No.	Capacity	Lid Size	Width	Height	Length	Wt.
RV 47024	15 Gallon	5"	12"	15"	25"	35 lbs.
RV 47022	30 Gallon	5"	19"	20"	25"	16 lbs.
RV 47013	50 Gallon	5"	19"	20"	38"	23 lbs.
RV 47020	100 Gallon	5"	30"	26"	38"	42 lbs.
RV 47350	150 Gallon	10"	36"	26"	48"	63 lbs.
RV 47352	200 Gallon	10"	36"	35"	48"	80 lbs.

Call Toll Free For Prices

Below Ground Water Storage Tanks



Water Storage Tanks for below ground installations. Ideal for use with RO water for spot-free rinse systems or for Potable water storage. Constructed of one-piece, seamless polyethylene. Self-locking covers are standard. **850 gallon** tanks feature (1) 24" manhole with lid. **1150 gallon** tank features (2) 24" manholes with lids. **Note: Tanks are F.O.B. Factory.**

Part No.	Gallons	Size	Wt.
RT AST850-1W	850	70"L x 60"W x 60"H	259 lbs.
RT AST1150-1W	1150	101"L x 60"W x 60"H	414 lbs.

Call Toll Free For Prices



H2O Water Only Vertical Tanks

These **Water Only Vertical Tanks** are free-standing for indoor or outdoor stationary applications. Designed for storage of water, or other liquids compatible with polyethylene and 1.0, or less specific gravity (8.34lbs/gal or less). Tanks are available in black, dark green, or mocha (some sizes). These tanks are made with FDA approved resin in NSF certified production plants. Sizes from 200 to 15,000 gallons. NSF Certified tanks.



Part No.	Gallons	Dimensions	Outlet Fitting	Lid
SN W94203-W	1100	86" D x 53" H	2" Bottom, 1.5" Top	18"
SN W94204-W	1500	86" D x 70" H	2" Bottom, 1.5" Top	18"
SN W94205-W	2500	90" D x 106" H	2" Bottom, 1.5" Top	18"
SN W94206-W	3000	102" D x 98" H	2" Bottom, 1.5" Top	18"