



Spraying Systems

**CLEANING NOZZLES**




**300 to 5000 PSI**

**High Quality, High Impact Spray Nozzles** for wands, arches, conveyor systems and anywhere high pressure washing or rinsing is needed. Available from 0 degree solid stream to 110 degree flat fan patterns. Stainless steel construction rated between 300 and 4000 PSI. Internal guide vane is available on some nozzle types to provide maximum spray integrity. Available in 1/8" male, 1/4" male, 1/4" female and 1/4" quick coupler styles as noted below. (See Nozzle Charts in back of this catalog for flow PSI)

**NOTE: Available in NPT Thread Only - NO BSP Thread available from Dultmeier Sales**

**MEG • WEG**



**WashJet MEG Series** 400 hardened stainless steel nozzles are rated to 3000 PSI. Available with or without stabilizer vanes. Solid stream to 65 degree wide patterns are available with and without vanes.


**1/8" MEG (Male)** Nozzles are available for #1 through #20 orifices. Male threads only. **Example: 1/8MEG0002 is 1/8" MPT (male) thread, zero stream, #2 orifice.** (ADD VA at end of number if internal vane is required).

**1/4" MEG (Male) or 1/4" WEG (Female)** nozzles are available from #2 through #80 orifices. **Example: 1/4WEG4004 is 1/4" female thread, 40 degree pattern, #4 orifice.** (ADD VA at end of number if internal vane is required).

Part No.	Nozzle Type	Max. PSI
SS 1/8MEGxxxx	1/8" Male, <b>No Vane</b>	3000
SS 1/8MEGxxxxVA	1/8" Male, <b>With Vane</b>	3000
SS 1/4MEGxxxx	1/4" Male, <b>No Vane</b>	3000
SS 1/4MEGxxxxVA	1/4" Male, <b>With Vane</b>	3000
SS 1/4WEGxxxx	1/4" Female, <b>No Vane</b>	3000
SS 1/4WEGxxxxVA	1/4" Female, <b>With Vane</b>	3000

**5% Discount on 20 Nozzles of One Size  
10% Discount on 100 Assorted Nozzles**

**IMEG**



**IMEG Series** 400 hardened stainless steel nozzles are rated to 4000 PSI. Unique design offers at least 25% more impact than regular MEG nozzles at comparable pressures. 5 to 80 degree wide patterns are available with and without vanes.

**1/8" IMEG (Male)** Nozzles are available from #3 through #8 orifices.

**1/4" IMEG (Male)** Nozzles are available from #2 through #8 orifices

Part No.	Nozzle Type	Max. PSI
SS 18IMEGxxxx	1/8" IMEG, <b>No Vane</b>	4000
SS 18IMEGxxxxVA	1/8" IMEG, <b>With Vane</b>	4000
SS 14IMEGxxxx	1/4" IMEG, <b>No Vane</b>	4000
SS 14IMEGxxxxVA	1/4" IMEG, <b>With Vane</b>	4000

**5% Discount on 20 Nozzles of One Size  
10% Discount on 100 Assorted Nozzles**

**QCMEG Series** 400 hardened stainless steel nozzles are rated to 4000 PSI. This series features 1/4" male quick coupler inlet and color coded caps. All QCMEG nozzles also come with internal stabilizer vanes. Solid stream to 40 degree wide patterns are available.

**5% Discount on 20 Nozzles of One Size and  
10% Discount on 100 Assorted Nozzles**



Part No.	Nozzle Type	Max. PSI
SS QCMEGxxxx	1/4" <b>Quick Coupler</b>	4000
SS QCCEM2540	1/4" <b>Brass Soap Nozzle</b>	300

**Note:** Nozzle colors are based on pattern and not orifice numbers.  
**Spray Angles:** 0° = Red 15° = Yellow 25° = Green 40° = White

**Nozzle Types**

**VVSS • USS**

**Spraying Systems VeeJet VVSS and USS Series 303** stainless steel nozzles create a very precise pattern from 300 to 1000 PSI. Solid stream to 110 degree wide patterns are available in a larger number of orifice sizes and flow rates.

**HVSS Series** are available from #1 through #9 orifices in 1/8" MPT or 1/4" MPT.

**HUSS Series** are available from #10 through #50 orifices in 1/8" MPT (not all patterns) and #10 through #80 in 1/4" MPT.

**(Sizing Example: H1/4VVSS2506 is 1/4" MPT, 25 degree pattern, #6 orifice).**



Part No.	Nozzle Type	Max. PSI
SS H1/8VVSSxxxx	1/8" Male	1000
SS H1/4VVSSxxxx	1/4" Male	1000
SS H1/4USSxxxx	1/4" Male	1000

**5% Discount on 20 Nozzles of One Size or  
10% Discount on 100 Assorted Nozzles**

**FLAT BACK**

**Spraying Systems TP Series Flat Back Spray Nozzles** do not have threads. Designed to be used with optional bodies and caps shown. Available in 0, 15 and 25 degree patterns in a wide variety of orifices. Rated from 300-3,000 PSI. Hardened, stainless steel construction. (Nozzles, bodies, caps, gaskets and strainers all sold separately).

**EG Series** nozzles include internal guide vane for a more precise pattern.  
**HSS Series** are standard nozzles without guide vanes. (Specify required pattern orifice).

Part No.	Vaness	Max. PSI
SS TPxxxEG	Yes	3000
SS TPxxxHSS	No	3000
SS CP7890SS	Stainless Cap.....	
SS CP11432SS	1/4" FPT SS Body - Requires Gaskets ...	
SS CP4743-NY	Body Gasket .....	
SS CP7894-TEF	Nozzle Gasket .....	
SS 8536-100	Stainless Strainer....	

\* Nozzle, Body, Cap, Strainer & Both Gaskets Will Make An Assembly.  
— Quantity Discounts Available —

**Hardened Stainless Spray Nozzles**

— Rated to 5,000 PSI —

**Stainless Steel, High Pressure Spray Nozzles** from *General Pump*. Higher pressure rating than other common nozzles. 0,15,25 and 40 degree patterns in 2-10 orifice sizes. **400 Series** hardened stainless orifices with 303 stainless bodies. **Made in USA.**



**S** suffix = 1/8" MPT. **Example:** 925060S = 25 Degree. 06 Orifice. 1/8" MPT  
**M** suffix = 1/4" MPT. **Example:** 940030M = 40 Degree. 03 Orifice. 1/4" MPT

Part No.	Pattern	* Size	Max. PSI
IP 900xx0S	0	1/8" MPT	5000
IP 915xx0S	15	1/8" MPT	5000
IP 925xx0S	25	1/8" MPT	5000
IP 940xx0S	40	1/8" MPT	5000
IP 900xx0M	0	1/4" MPT	5000
IP 915xx0M	15	1/4" MPT	5000
IP 925xx0M	25	1/4" MPT	5000
IP 940xx0M	40	1/4" MPT	5000

\* Replaced with Equivalent for 1/4 ACMEG Style Nozzles.