



## Kanaflex® 220RS All Weather Rubber Suction Hose

**220RS Rubber Suction and Discharge Hose** remains flexible at low temperatures. A great choice for vacuum pumping of septic tanks, car wash pits, etc. Ideal for rough, tough use around construction sites and industrial plants.

**Working Pressure:** to 150 PSI and full vacuum. **Temperature Range:** -40° F. to 158° F. The SBR (buna) material makes this hose extremely lightweight, flexible and easy to couple.

Part No.	I.D.	O.D.	Work Pressure	Lengths	100 ft. Wt. per
KA 220RS-3	3"	3.50"	43 PSI	100'	130 lbs.
KA 220RS-4	4"	4.57"	38 PSI	100'	200 lbs.
KA 220RS-6	6"	6.69"	23 PSI	60'	337 lbs.

**\* 25% Discount if Ordered in 100' Rolls**

Call  
Toll Free  
For  
Prices

## Kuriyama Thermo Plastic Suction Hose

**125PVC** is a general purpose PVC suction and discharge hoses for water and fertilizers. (PVC is not suitable for some agricultural chemicals - must use EPDM). Orange hose with extra UV inhibitor for methane gas recovery at landfills. Available in 3 sizes with internal ID to mate with OD of rigid pipe. Full vacuum rating to 4" at 72° F. **Temperature Range:** -13° F. to +158° F. This hose becomes stiff at low ambient temperatures.



NOTE: CUT LENGTHS SOLD  
IN 5' INCREMENTS ONLY

Part No.	I.D.	O.D.	PSI@ 68° F	Std. Pkg.	Wt/C	Std. Pkg. Discount
TF 125PVC-3/4	3/4"	.95"	100	100'	18	25%
TF 125PVC-1	1"	1.25"	75	100'	24	25%
TF 125PVC-1-1/4	1-1/4"	1.47"	75	100'	31	25%
TF 125PVC-1-1/2	1-1/2"	1.75"	65	100'	38	25%
TF 125PVC-2	2"	2.27"	60	100'	56	25%
TF 125PVC-2-1/2	2-1/2"	2.84"	60	100'	67	25%
TF 125PVC-3	3"	3.35"	60	100'	99	25%
TF 125PVC-4	4"	4.45"	50	100'	146	25%
TF 125PVC-5	5"	5.55"	35	50'	240	25%
TF 125PVC-6	6"	6.67"	35	100'	284	25%

## Clear Vinyl Tubing Transparent, Non-Toxic Flexible

**Clear Vinyl Tubing** is flexible, lightweight and transparent. Provides full flow viewing. Construction is Polyvinyl Chloride (PVC). Ideal for handling a wide variety of liquids. Excellent resistance to many types of acids, detergents

and alkalis. Formulated to comply with FDA requirements. Rated from +25° to 150° F. **Sold in rolls only, no cut lengths.**

Part No.	I.D.	O.D.	Wall	Max. PSI @ 70° F	Roll Size
TF 1A	1/8"	1/4"	1/16"	65	100'
TF 1	1/4"	3/8"	1/16"	50	100'
TF 1X500	1/4"	3/8"	1/16"	50	500'
TF 2	3/8"	1/2"	1/16"	40	100'
TF 2X500	3/8"	1/2"	1/16"	40	500'
TF 2A	3/8"	9/16"	3/32"	50	100'
TF 4A	1/2"	5/8"	1/16"	25	100'
TF 4	1/2"	3/4"	1/8"	45	100'
TF 6	5/8"	13/16"	3/32"	30	100'
TF 5	5/8"	7/8"	1/8"	40	100'
TF 7	3/4"	1"	1/8"	35	100'
TF 9	1"	1-1/4"	1/8"	25	100'
TF 11	1-1/4"	1-1/2"	1/8"	20	50'
TF 13	1-1/2"	1-3/4"	1/8"	16	50'
TF 13A	1-1/2"	2"	1/4"	35	50'
TF 15	2"	2-1/2"	1/4"	30	50'

www.  
dultmeier.com  
We now have  
our Catalogs as well as  
Parts Schematics online!



## Kanaflex® Dryer Blower Hose 100% EPDM With a wire Helix Superior to 2-Ply Cotton or Polyester

**Abrasion Resistant, Wire-braid Blower or Dryer hose.**

EPDM construction with **internal wire braid**. Tough, yet still flexible. Ideal for industries where abrasive applications are required. Rated to 220° F. Ideally suited for Hot Air Dryers.

Smooth bore, excellent weatherability. Wear-life is superior to standard 2-ply cotton/poly ducting hose.



Part No.	I.D.	O.D.	* Std.Pkg.	Weight Per Foot
KA 620WD-4	4"	4.39"	50'	.73 lbs.
KA 620WD-5	5"	5.43"	50'	.84 lbs.
KA 620WD-6	6"	6.36"	50'	1.04 lbs.
KA 620WD-8	8"	8.35"	50'	1.38 lbs.
KA 620WD-10	10"	10.45"	50'	2.40 lbs.
KA 620WD-12	12"	12.40"	25'	2.50 lbs.

Call  
Toll Free  
For  
Prices

**\*25% Discount allowed on Standard Packages.**

### DUCT CLAMPS for 620WD HOSE

Part No.	For	ID Hose Size....
KA DC4	For 4"	ID Hose Size....
KA DC5	For 5"	ID Hose Size....
KA DC6	For 6"	ID Hose Size....
KA DC8	For 8"	ID Hose Size....
KA DC10	For 10"	ID Hose Size....
KA DC12	For 12"	ID Hose Size....



## Kanaflex® Ducting/Blower Hose Heavy Duty Use

100% EPDM with a Polyethylene Helix



For heavy duty ducting and blower applications. 100% EPDM Rubber with polyethylene braids, smooth bore, thicker side wall for more abrasion resistance. Corrugated OD. Temperature to 158° F.

Part No.	I.D.	O.D.	* Std.Pkg.	Weight Per Foot
KA 630ED-4	4"	4.53"	50'	.76 lbs.
KA 630ED-6	6"	6.56"	50'	1.00 lbs.
KA 630ED-8	8"	8.66"	50'	1.37 lbs.

Call  
Toll Free  
For  
Prices

**\* 25% Discount allowed on Standard Packages.**

## Kuriyama Blower Ducting Hose

**Thermo-Duct™ Hose** is the ideal choice for demanding and difficult applications such as blower and ducting use.

**Features:** Helical wire reinforced design  
• Superior chemical, moisture and weathering resistance  
• Thermoplastic/rubber construction  
• 30 Mil wall thickness provides excellent internal and external abrasion resistance  
• Rated from -60° to +275° F.



**— 25' Minimum Order —**

Part No.	I.D.	Maximum PSI	Vacuum Rating	* Std. Pkg.
TF TMOD200	2"	17	24	25'
TF TMOD300	3"	14	24	25'
TF TMOD400	4"	11	24	25'
TF TMOD600	6"	9	9	25'
TF TMOD800	8"	8	8	25'
TF TMOD1000	10"	7	6	25'
TF TMOD1200	12"	6	4	25'