FILL-RITE 12 Volt Fuel Pumps

Standard Pumps will Handle E10 & B20 Fuels. Any Mixtures Higher than This See Adjacent Page for Conversion Kits

Fill-Rite fuel transfer pumps and meters are currently designed to handle a maximum blend ratio of 1-20% biodiesel fuel. These mixtures of fuels are known as B1-B20. Conversion kits are available to make Fill-Rite pumps compatible with biodiesel blend ratios from above 20% (B20) all the way up to the 100% concentrate (B100) and also for E85 fuel. (see next page). Also see "BD" Models for B21-B100.



FILL-RITE 1200 & 610 Series 12 & 115 Volt Pumps have been the standard of — built for long service under tough operating conditions.
 Complete with 3/4" x 12' hose with nozzle, 1" telescoping (20" - 34") steel suction pipe, 15 ft. power cable and with or without meter.

 UL L Bron 1/4 H 	isted.	Self Primin Check Valv	e & Strainer.
Part No. FR 1210 FR 1211	12-Volt DC Fuel Pump Less M 12-Volt DC Fuel Pump With 8(<u>Wt.</u> 35 lbs. 40 lbs.
FR 610H	115-Volt Fuel Pump Less Met	er	28 lbs.
FR 807CMK FR 807CN-1	Meter Kit with Fittings to Add I		
FR 507CIN-1	* Meter Kit for Biodiesel (B20 Repair Kit for 1210 Pump		

ct.

FR4210

FR4410

RE let 4200 Series

Replacement 1" Suction Pipe (Adj. 20" to 34.75") FR 151-98 Use for B21-B100 Biodiesel Only.

FILL-RITE **Fuel Pumps Heavy Duty** 12 & 24-VOLT

These fuel pumps are ideal for use with gas, diesel, kerosene, E15 & B20 and petroleum based products.

- Automatic ByPass Valve, Check Valve & Strainer
- 2" Bung Adapter, 1" Telescoping Suction Pipe (22-40")
- 18' Power Cord

- Carbon Vanes & Seals
- Explosion-Proof 1/4 HP UL Listed Motor
- 30 Minute Duty Cycle No Bearing Lubrication
- Required
- Manual Nozzle Included.

1" x 12 ft. hose and nozzle on 12-volt and 24 volt. 20 GPM maximum flow (18 GPM with 1" meter). All pumps can be equipped with a meter kit.

Part No.		Wt.
FR FR4210	12-Volt Pump w/Hose & Nozzle	36 lbs.
FR FR4410	24-Volt Pump w/Hose & Nozzle	36 lbs.
FR 807CMK	3/4" Meter Kit for FR4410	7 lbs.
FR 901MK4200	1" Meter Kit for 4200/4400	7 lbs.
FR F8739	Repair Kit for FR4210 & FR4410	2 lbs.

array of design adv performance to unpr	ancements, technolo ecedented levels. Inte	, ogies and ι	tec Intelligence Iser functionalitie s™inform when a	es that take
Standard Feature	s:		NX25-12V-PO	NX25-12
 Continuous Duty 		low Rate	25 GPM	25 GPM
25 GPM with Aut		Voltage	12 to 24V DC	12 to 24V E
12 to 24V DC		let/Outlet	1-1/4" - 1" NPT	1-1/4" - 1" M
Lower Amp Draw		lounting	2" Bung (NPT)	2" Bung (N
		mp Draw	29 Amps	29 Amps
Lightweight		otor Power	1/3 HP	1/3 HP
 Auto Power Down 		ompatible Fuels	Diesel, Gasoline, E E15, Kerosene, Mi	
 Magnetic Switch 	Ac	cessories	20' Power Cord.	20' Power C
(Replaceable)			20 1 0000 0010.	18' Hose
 Improved Suctio 	n			1" Ultra Hi
 Lift. Suction Pipe Removable Powe 	e Sold Separately	(ALBER	IT /	Flow Nozz
Intelligent Tones				
WARRANTY				NX25-12V
	Super High Flow Pum 12-Volt NX Pump Ol	-		
Part No.		ŇLY	<u>W</u> 	<u>t.</u>
Part No. FR NX25-12V-PO	12-Volt NX Pump Ol 12-Volt NX Fuel Pun	NLY np, Automat	<u>w</u> 	<u>t.</u> Ibs
Part No. FR NX25-12V-PO	12-Volt NX Pump Ol	NLY np, Automat	<u>W</u> 	<u>t.</u>

FILL-RITE

FILL-RITE FR8 Series Fuel Pumps

12-Volt DC • 8 GPM • Compact & Lightweight

FILL-RITE FR8 Series 12-Volt Fuel Pumps eliminate the hassle, spills, and wasted time caused by clunky and inefficient gas cans and bring the fueling efficiency of a gas station right to the job site. Compact, lightweight yet built to last, and offering true 8 GPM performance – the same as gas station pumps – the FR8 12-volt fuel pump is ideal for mobile fueling of equipment with 2-25-gallon fuel tanks such as offroad vehicles, lawn mowers and landscape equipment, and small construction machinery.

These 12-volt *FILL-RITE* fuel pumps feature the same proven reliability and quality construction found with all Fill-rite fuel pumps, including heavy-duty cast iron bodies, rotary vane technology, and thermally protected motors. Pumps also feature a lockable power switch for greater thet deterrence (*Master Lock®* and the print of the technology). padlock not included). Duty cycle of 15 min. On / 15 min. Off for TWICE-as-fast, cost-saving fueling efficiency within a 45-minute span.



12-Volt Pump w/Hose & Nozzle 12 lbs.

12-Volt Pump Only 12 lbs.

IND CW

FR 8

FR 8-PX