

PVC Air/Water Hose Assemblies

Ideal for Medium Duty Air & Water Applications

Industrial Air/Water Hose Assemblies. Looks and feels like rubber. Low temperature flexibility. Reinforced PVC construction. Ideal for medium-duty air and water applications. Rated to 300 PSI at 70° F. Standard with 1/4" male x male fittings on all sizes. Rated from +25° to +150° F. **Made in the USA.**



Part No.	Size	Color
TF KF2-R025CP	1/4" x 25'	Red
TF KF2-R050CP	1/4" x 50'	Red
TF KF2-R100CP	1/4" x 100'	Red
TF KF3-R025CP	3/8" x 25'	Red
TF KF3-R050CP	3/8" x 50'	Red
TF KF3-R100CP	3/8" x 100'	Red

Rubber Air Hose Assemblies



- Lightweight & Super Strong
- Ozone Resistant Cover Protects from Weather
- Rated from -40° F. to +190° F., & 300 PSI
- Brass 1/4" MPT Fittings
- Abrasion & Kink Resistant
- Bend Restrictor Guards
- Oil Resistant Cover



Part No.	Hose	Wt.
DU AH25	3/8" x 25'	2.7 lbs.
DU AH50	3/8" x 50'	5.3 lbs.
DU AH100	3/8" x 100'	10.6 lbs.

Bulk Air/Water Hose Kuriyama

- Rated to 300 PSI @ 70° F. 200 PSI on 3/4"
- Blue PVC
- Abrasion Resistant
- Lightweight & Flexible
- One Piece Reels
- Temperature Rating: 15° F. to 150° F.

Cut Lengths in 5' Increments.




Part No.	I.D.	O.D.	Feet Per Reel	Wt. Per Reel
TF K1156-1/4	1/4"	.500"	500'	44 lbs.
TF K1156-3/8	3/8"	.625"	500'	56 lbs.
TF K1156-1/2	1/2"	.750"	500'	70 lbs.
TF K1156-3/4	3/4"	1.030"	300'	72 lbs.

25% Discount for Full Reel Purchase

Spray & Chemical Transfer Hose

800 PSI • Rubber Blend • Polyethylene Lined

Kuritech Truespray Will Reduce Unwanted Herbicide Damage



Much less retention/absorption of Dicamba with this polyethylene lined rubber blend hose when compared to other rubber/PVC/EPDM hoses. The permeation-resistant inner liner provides superior clean out. Field tests show a significant reduction in yield loss from herbicide carryover. Pin-pricked cover vents trapped gases to help prevent ballooning.


Excellent for agricultural chemicals, high pressure tree spraying, paints and solvents. Blue cover is standard (black available - call for details) and available in 100/300 foot package only - **NO CUTS**. 800 PSI and 400 PSI on 1", -40° F. to 130° F. Use standard poly/stainless hose barb fittings with outside clamps.

Do Not Use Hydraulic Fittings on this Hose.

Part No.	Size	Length	Wt.
TF A4086-06X100	3/8"	100'	11 lbs.
TF A4086-06X300	3/8"	300'	33 lbs.
TF A4086-08X100	1/2"	100'	15 lbs.
TF A4086-08X300	1/2"	300'	45 lbs.
TF A4086-12X100	3/4"	100'	24 lbs.
TF A4086-12X300	3/4"	300'	72 lbs.
TF A4086-16X100	1"	100'	32 lbs.
TF A4086-16X200	1"	200'	65 lbs.

Please remember there are No Returns on customer specified cut lengths of hose.

General Purpose Air/Water Hose



ATH Series Industrial Air/Water Hose. Polyvinyl Chloride (PVC) construction with polyester yarn braided reinforcement. Formulated for medium-duty industrial applications at temperatures from +25° to +150° F. Sold by the foot or in standard packages at lower pricing. Color is Blue, except for 5/8" which is Red. Made in USA. **Cut Lengths in 5' Increments.**

Part No.	I.D.	O.D.	Max PSI @ 70° F.	Std. Pkg.	* Std. Pkg. Discount
TF ATH-0140B	1/4"	.500"	300	300'	25%
TF ATH-0380B	3/8"	.625"	300	300'	25%
TF ATH-0120B	1/2"	.750"	300	300'	25%
TF ATH-0580R	* 5/8"	.875"	250	300'	25%
TF ATH-0340B	3/4"	1.06"	250	300'	25%
TF ATH-1000B	1"	1.33"	250	200'	25%

* Red.

*** 25% Discount for Standard Packages**

Kuriyama **POLYAIR Air/Water Hose** *Bulk or Assemblies*



A very flexible air/water hose. The PVC blending makes this hose look and feel like a rubber hose. Stays flexible at low temperatures.

Features: Lightweight and easily recoiled after use • Can be used for outdoor low temperature applications • Non-marking cover • PVC cover and tube with spiral braid polyester yarn • Temperature Rating from -15° F. to +150° F. • Stocked in red • UV resistant • Solid x Swivel ends on all assemblies. Available in grey, blue and yellow - *Call for Details.* **Cut Lengths in 5' Increments.**

Part No.	I.D.	O.D.	PSI @ 70° F.	Std. Pkg.	Wt. Per Reel
TF K1134-1/4	1/4"	.500"	300	500	44 lbs.
TF K1134-3/8	3/8"	.625"	300	500	58 lbs.
TF K1134-1/2	1/2"	.813"	300	500	93 lbs.
TF K1134-3/4	3/4"	1.125"	250	300	96 lbs.
TF K1134-1	1"	1.406"	250	300	123 lbs.
TF AH-3/4X25	3/4" x 25'	Red Air Hose, 3/4" MPT			
TF AH-3/4X50	3/4" x 50'	Red Air Hose, 3/4" MPT			
TF AH-3/4X100	3/4" x 100'	Red Air Hose, 3/4" MPT			
TF AH-1X25	1" x 25'	Red Air Hose, 1" MPT			
TF AH-1X50	1" x 50'	Red Air Hose, 1" MPT			
TF AH-1X100	1" x 100'	Red Air Hose, 1" MPT			

*** 25% Discount for Full Reel Purchase**


Oil Resistant Air Hoses

Oilshield Air Hoses are 100% Nitrile rubber construction and have a Class A oil resistant rating. 30% lighter weight than traditional air hoses but with added flexibility and strength. The perfect choice where hoses come in contact with oil, diesel, gasoline and cleaning agents. Unique cover will even stand up to welding splatter and grinding sparks.

Ozone resistant, Flame and spark resistant, Abrasion resistant, Kink Resistant. Standard with bend restrictors and 3/8" mpt solid brass fittings with 1/4" reducers for most any application. Rated to 300psi and -30° F to +180° F.

Part No.	Size	* Std Pack	Wt.
RX OS3835	3/8" x 35'	5	3 lbs.
RX OS3850	3/8" x 50'	4	5.5 lbs.
RX OS38100	3/8" x 100'	3	11 lbs.
RX OS1250	1/2" x 50'	4	7 lbs.
RX OS12100	1/2" x 100'	2	14 lbs.

*** 5% Discount for Orders in Standard Packs**



3 YEAR WARRANTY

