

Black Steel Pipe

Schedule 40 & Schedule 80



Welded and Seamless Black Steel Pipe. Available in threaded and coupled, (TC) or plain end (PE). *T/C Style*

Welded SCH Pipe is available in Sch40 Grade A53A or Sch80 Grade A53B. Welded pipe is **"Not for Use with LP or NH3"**.

Seamless SML Pipe is available in Sch40 or Sch80 Grade A106B. Rated for use with LP or NH3 for Sch40 if used with weld fittings or SCH80 if used with forged steel thread fittings or weld fittings.

Welded and seamless pipe sizes are sold in 20 ft. or 21 ft. lengths only as noted, no cut pieces. **(Special make nipples which are threaded both ends are also available).**

WELED PIPE

Part No.	I.D. Size	Grade	Ends	Wt.	Length	Per Ft. Net Ea.
US SCH40-1/2TC	1/2"	A53A	T/C	18 lbs.	21'	
US SCH40-3/4TC	3/4"	A53A	T/C	24 lbs.	21'	
US SCH40-1TC	1"	A53A	T/C	35 lbs.	21'	
US SCH40-1-1/4TC	1-1/4"	A53A	T/C	48 lbs.	21'	
US SCH40-1-1/2TC	1-1/2"	A53A	T/C	57 lbs.	21'	
US SCH40-2TC	2"	A53A	T/C	77 lbs.	21'	
US SCH40-1PE	1"	A53A	PE	35 lbs.	21'	
US SCH40-1-1/4PE	1-1/4"	A53A	PE	48 lbs.	21'	
US SCH40-1-1/2PE	1-1/2"	A53A	PE	57 lbs.	21'	
US SCH40-2PE	2"	A53A	PE	77 lbs.	21'	
US SCH40-3PE	3"	A53B	PE	159 lbs.	21'	
US SCH40-4PE	4"	A53B	PE	226 lbs.	21'	
US SCH40-6PE	6"	A53B	PE	398 lbs.	21'	
US SCH80-1-1/4PE	1-1/4"	A53A	PE	63 lbs.	21'	
US SCH80-1-1/2PE	1-1/2"	A53A	PE	76 lbs.	21'	
US SCH80-2PE	2"	A53B	PE	106 lbs.	21'	
US SCH80-3PE	3"	A53B	PE	215 lbs.	21'	
US SCH80-4PE	4"	A53B	PE	315 lbs.	21'	

SEAMLESS PIPE

Part No.	I.D. Size	Grade	Ends	Wt.	Length	Per Ft. Net Ea.
US SML40-1-1/4PE	1-1/4"	A106B	PE	48 lbs.	21'	
US SML40-1-1/2PE	1-1/2"	A106B	PE	57 lbs.	21'	
US SML40-2PE	2"	A106B	PE	77 lbs.	21'	
US SML40-3PE	3"	A106B	PE	159 lbs.	21'	
US SML80-1PE	1"	A106B	PE	43 lbs.	21'	
US SML80-1-1/4PE	1-1/4"	A106B	PE	60 lbs.	21'	
US SML80-1-1/2PE	1-1/2"	A106B	PE	76 lbs.	21'	
US SML80-2PE	2"	A106B	PE	106 lbs.	21'	
US SML80-3PE	3"	A106B	PE	215 lbs.	21'	
US SML80-4PE	4"	A106B	PE	305 lbs.	21'	

PVC Pipe

Schedule 80 Full Length

Grey PVC Plastic Pipe is supplied in 20 ft. lengths with plain ends. Heavy-wall construction can be threaded or glued. Maximum temperature is 140° F. *(Sold in lengths only, no cut pieces).*



Part No.	Pipe Size	* Max. Pressure	Std. Length
KE 1/2-PVC	1/2"	850	20'
KE 3/4-PVC	3/4"	690	20'
KE 1-PVC	1"	630	20'
KE 1-1/4-PVC	1-1/4"	520	20'
KE 1-1/2-PVC	1-1/2"	470	20'
KE 2-PVC	2"	400	20'
KE 3-PVC	3"	370	20'
KE 4-PVC	4"	320	20'
KE 6-PVC	6"	280	20'

* Pressure Rating at 73° F. Substantial drop off at higher temperatures.

Steel Pipe Wrap & Primer


Protects underground steel pipe from corrosion. (1) Quart Primer covers approximately 23' of 3" pipe or 33' of 1-1/4" pipe. (1) 4" Wrap Roll (12 mil thick) covers approximately 44' of 2" pipe or 31' of 3" pipe. (1) 2" Wrap Roll (35 mil thick) covers approximately 23' of 1-1/4" pipe. **Always use primer with wrap.**



Part No.	Description
DU TAP2	2" x 50' Roll XTRU Coat Wrap
DU TAP4	4" x 100' Roll XTRU Coat Wrap
DU TAPP	1 Quart XTRU Coat Primer.....

Pipe Clamps & Struts

Support piping runs for steel or HDPE. The 12 gauge galvanized channels have mounting holes; 1-5/8" x 1-5/8". 20' lengths. Galvanized clamps include nut and bolt.



PS200EH

Part No.	Pipe Size	Description
KE PS200EH	-	Galvanized Channel, 20 ft.
KE B2010	1"	1" Pipe Clamp
KE B2012	1-1/2"	1-1/2" Pipe Clamp
KE B2013	2"	2" Pipe Clamp
KE B2015	3"	3" Pipe Clamp
KE B2017	4"	4" Pipe Clamp
KE B2020	6"	6" Pipe Clamp

304 Stainless Steel Pipe

Schedule 10 • Schedule 40



Ideal for Chemical Run Lines. Sch10 pipe requires welded connections and cannot be threaded. Sch40 pipe can be threaded or welded. All sizes are plain end. Sold in 20' lengths. **No Cut Pieces.**


Part No.	Pipe Size	Grade	Ends	Wt.	Length	Per Ft. Net Ea.
US SCH10-304-050	1/2"	Sch. 10	PE	17 lbs.	20'	
US SCH10-304-075	3/4"	Sch. 10	PE	23 lbs.	20'	
US SCH10-304-110	1"	Sch. 10	PE	34 lbs.	20'	
US SCH10-304-114	1-1/4"	Sch. 10	PE	45 lbs.	20'	
US SCH10-304-115	1-1/2"	Sch. 10	PE	54 lbs.	20'	
US SCH10-304-200	2"	Sch. 10	PE	73 lbs.	20'	
US SCH10-304-300	3"	Sch. 10	PE	151 lbs.	20'	
US SCH10-304-400	4"	Sch. 10	PE	216 lbs.	20'	
US SCH10-304-600	6"	Sch. 10	PE	379 lbs.	20'	
US 304SS-1/2	1/2"	Sch. 40	PE	17 lbs.	20'	
US 304SS-3/4	3/4"	Sch. 40	PE	23 lbs.	20'	
US 304SS-1	1"	Sch. 40	PE	34 lbs.	20'	
US 304SS-1-1/4	1-1/4"	Sch. 40	PE	45 lbs.	20'	
US 304SS-1-1/2	1-1/2"	Sch. 40	PE	54 lbs.	20'	
US 304SS-2	2"	Sch. 40	PE	73 lbs.	20'	
US 304SS-3	3"	Sch. 40	PE	151 lbs.	20'	
US 304SS-4	4"	Sch. 40	PE	216 lbs.	20'	
US 304SS-6	6"	Sch. 40	PE	379 lbs.	20'	

Carbon Steel Weld Fittings

Schedule 40


90° Elbows

Long Radius



Part No.	Size
US WL90-1-1/2	1-1/2"
US WL90-2	2"
US WL90-3	3"
US WL90-4	4"
US WL90-5	5"
US WL90-6	6"

45° Elbows



Part No.	Size
US WL45-2	2"
US WL45-3	3"
US WL45-4	4"
US WL45-5	5"
US WL45-6	6"

TEES




Part No.	Size
US WT-2	2"
US WT-3	3"
US WT-4	4"
US WT-5	5"
US WT-6	6"

CAPS



Part No.	Size
US WCA-2	2"
US WCA-3	3"
US WCA-4	4"
US WCA-5	5"
US WCA-6	6"

Reducers



Part No.	Size
US WRED-3X2	3" x 2"
US WRED-4X2	4" x 2"
US WRED-4X3	4" x 3"
US WRED-5X4	5" x 4"
US WRED-6X4	6" x 4"
US WRED-6X5	6" x 5"

Crosses



Part No.	Size
US WCR-2	2"
US WCR-3	3"
US WCR-4	4"

Working Pressure Ratings in PSI for Carbon Steel Butt Weld Fittings, Schedule 40

1"	1-1/2"	2"	3"	4"	5"	6"
1575	1005	900	1095	975	885	840

All Ratings at -20° to +650° F.