

Goodall Stainless NH3 Hose

Goodall NH3 Hose is warranted for the demands of Anhydrous Ammonia service. Built to handle working pressures of 350 PSI with a 1750 PSI minimum burst pressure.

Note: Ammonia hose is sold only for use in the agricultural industry as a transfer hose. It is not intended for use in the refrigeration market or as a component in a fixed or permanent piping system. All hose assemblies receive hydrostatic testing to 700 PSI for 5 minutes. **Goodall** Ammonia hose is sold as coupled assemblies with crimped end connections. **Hose is not available in bulk uncoupled lengths.**

N2595 Stainless Braid Butyl Tube - Neoprene Cover - Black



N2595 is a super premium hose with an 8-Year removal date, 8-Year service life and an 8-Year prorated warranty. Butyl tube and black neoprene cover. Stainless braid. **Not for industrial use.**



Fitted NH3 Hose Assemblies

N1446 Stainless Steel Braid Butyl Tube - Neoprene Cover - Green Stripe



N1446 is a super premium hose with a 10-Year removal date, 10-Year service life and a 10-Year prorated warranty with a full warranty for the first 5 years. Butyl tube and black neoprene cover with green spiral stripe. Stainless braid. Recommended for riser use and other high stress applications. **Note: N1446 is no longer available in 1-1/2" sizes.**

FITTED HOSE ASSEMBLIES

Part No.	ID	MPT	Length	Wt.
GD N2595-1X10	1"	1"	10'	10 lbs.
GD N2595-1X12	1"	1"	12'	12 lbs.
GD N2595-1X15	1"	1"	15'	13 lbs.
GD N2595-1X20	1"	1"	20'	18 lbs.
GD N2595-114X10	1-1/4"	1-1/4"	10'	16 lbs.
GD N2595-114X12	1-1/4"	1-1/4"	12'	18 lbs.
GD N2595-114X15	1-1/4"	1-1/4"	15'	20 lbs.
GD N2595-114X20	1-1/4"	1-1/4"	20'	22 lbs.
GD N1446-1X15	1"	1"	15'	13 lbs.
GD N1446-2X100	2"	2"	100'	190 lbs.
GD 2191	DOT Tag & Testing			

**CALL
for
CURRENT
PRICING**

Hose Assemblies are standard with MPT end connections. Female End Connections (TF16, TF20, TF32) also Available.

— Custom Lengths Available for Fitted NH3 Hose —

N-Serve Hose Assemblies



Part No.	Description
GP 4700-1/2X15	1/2" X 15' OAL, Fixed MPT, 316SS Ends
GP 4700-1/2X20	1/2" X 20' OAL, Fixed MPT, 316SS Ends

FOLLOW US ON
FACEBOOK

@Dultmeier Sales



Parker 7262 Anhydrous Ammonia Hose Assemblies

Parker's Series 7262 Anhydrous Ammonia Hose provides superior service in agricultural applications. The braided textile reinforcement provides corrosion and kink resistance for operator safety. The cover features dual green stripes for easy identification, resists abrasion, chemicals and weathering for maximum durability and performance. **Series 7262** is qualified with permanent crimp couplings for a safe and secure connection and provides robust service in challenging applications.

FEATURES/BENEFITS:

- Tube:** Black EPDM for chemical resistance to 180° F.
- Reinforcement:** Multiple textile braids for corrosion and kink resistance, strength & durability.
- Cover:** Black EPDM for abrasion and chemical resistance (*perforated wrapped cover*).
- Cover:** Dual green longitudinal stripes for easy identification.
- Couplings:** Qualified with steel crimp couplings for a durable, safe & secure connection.

MARKETS:

- Agriculture

APPLICATIONS:

- Anhydrous ammonia (NH3) usage for bulk plants and storage facilities.
- In-plant transfer.
- Farm NH3 fertilizing equipment & systems.
- Commercial & industrial refrigeration equipment supply lines. (*Outdoor Use Only*)

INDUSTRY STANDARDS:

- ARPM IP-14

SAFETY / TECHNICAL / SPECIFICATIONS:

- Design Factor:** 5:1
- Maximum Working Pressure:** 350 PSI
- Maximum Burst Pressure:** 1750 PSI
- Operating Temperature Range:** -40° F. to 180° F.
- For Anhydrous Ammonia use ONLY.** Do not use in Liquid Petroleum Gas (LPG) / Propane or Natural Gas applications. Use only with couplings qualified by Parker. Do Not Use with couplings containing hidden o-rings such as male swivel couplings. For non-agricultural or refrigeration applications, contact *Dultmeier Sales* or *Parker*.



**Nylon Green Stripe
Each End is Marked Per
Manufacturers Requirement**

Stainless Hose Also Available



Hoses are Strapped for Easy
Handling & Stocking

Part No.	I.D.	O.D.	Ends	Length	Bend Radius
ST AN05015	1/2"	.095"	1/2" MPT	15'	5"
ST AN05025	1/2"	.095"	1/2" MPT	25'	5"
ST AN075015	3/4"	1.25"	3/4" MPT	15'	8"
ST AN10003	1"	1.51"	1" MPT	3'	10"
ST AN10005	1"	1.51"	1" MPT	5'	10"
ST AN10010	1"	1.51"	1" MPT	10'	10"
ST AN10012	1"	1.51"	1" MPT	12'	10"
ST AN10015	1"	1.51"	1" MPT	15'	10"
ST AN10020	1"	1.51"	1" MPT	20'	10"
ST AN12503	1-1/4"	1.78"	1-1/4" MPT	3'	12"
ST AN12505	1-1/4"	1.78"	1-1/4" MPT	5'	12"
ST AN12510	1-1/4"	1.78"	1-1/4" MPT	10'	12"
ST AN12512	1-1/4"	1.78"	1-1/4" MPT	12'	12"
ST AN12515	1-1/4"	1.78"	1-1/4" MPT	15'	12"
ST AN12520	1-1/4"	1.78"	1-1/4" MPT	20'	12"
ST AN15010	1-1/2"	2.03"	1-1/2" MPT	10'	14"
ST AN15012	1-1/2"	2.03"	1-1/2" MPT	12'	14"
ST AN15015	1-1/2"	2.03"	1-1/2" MPT	15'	14"
ST AN15018	1-1/2"	2.03"	1-1/2" MPT	18'	14"
ST AN20015	2"	2.75"	2" MPT	15'	16"
ST AN20020	2"	2.75"	2" MPT	20'	16"