Squibb-Taylor NH3 Valves

NH₃ Valves



Liquid Fill or Vapor Valve

1-1/4" MPT x 1-3/4" Acme with plugged 1/4" FPT side port

The A525P consists of a service valve, a filling connection and an excess flow valve.

Filling Rate*

	DIFFERENTIAL PRESSURE, PSIG					
SERVICE	5	10	20	30	40	50
NH3	46 gpm	62 gpm	85 gpm	98 gpm	114 gpm	119 gpm
LP-gas	39 gpm	56 gpm	76 gpm	90 gpm	104 gpm	114 gpm

* Caution: 1.68" minimum I.D. dip tube must be used to obtain filling rates



Excess flow housing will not fit some older

tanks with small dip tube. Can convert

valves to fit these old style tanks by ordering valves with 1590-1100

old style excess flow

A520R

A520R & A521P

Liquid Withdrawal Valves

1-1/4" MPT x 1" FPT Outlet

Consist of a service valve and an excess flow valve

A520R has a built-in "Tri-Gard" internal relief valve that bleeds product back to the tank when hose pressure exceeds tank pressure by 50 PSI. In this way hose life is extended and chance of hose rupture is reduced.

A521P has a 1/4" FPT plugged side port which can be used for installation of a hydrostatic valve.

Valve No.	Withdrawal * Rate	Differential Closing Pressure
A520R & A521P	45 gpm	13 psig

* Caution: 1.68" minimum I.D. dip tube must be used to obtain withdrawal rates.

		10+
Part No.	<u>D</u> i	SCOUNT
ST A525P	Filler Valve	5%
ST A520R	Withdrawal Valve with internal Relief	5%
ST A521P	Withdrawal Valve	5%

- Discounts Not Assorted -



High Flow Valves for Riser Service Only

AR491NP-70 Liquid or Vapor Valve, 2" MPT by 1" FPT outlet. 1/4" Plug.

AR492NP-70 Liquid Withdrawal Valve, 2" MPT by 1-1/4" FPT outlet. 1/4" Plug.

Valve No.	Excess Flow Checks at:
AR491NP-70	70 gpm
AR492NP-70	70 gpm
A493NR-95	95 gpm
A494NR-110	110 gpm

A493NR-95 High

Volume Riser valve with 2" MPT x 1-1/4" FPT connections and fitted with a Hydrostatic relief. For Use with 1-1/4" hoses.

Part No.		10+ DISCOUNT
ST AR491NP-70	Riser Valve, 2" x 1", 70 GPM	5%
ST AR492NP-70	Riser Valve - 2" x 1-1/4", 70 GPM	5%
ST A493NR-95	Riser Valve 2" x 1-1/4", 95 GPM	5%
CT AAGAND 110	Dicor Valvo 2" v 1 1/4" 110 CDM	E0/

- Discounts Not Assorted -

Order from our entire inventory online! Scan our QR Code dultmeier.com



Web Specials

• Current Pricing • Current Flyers Order Status Parts Schematics



Hose End Valve - Aluminum -AL1520BF

5% Discount on 104

ST AL1520BF

End

SQUIBB TAYLOR 1" & 1-1/4" Hose End Globe Valves with bleeder valve and 6" Safety extension

(Acme) installed.

ACME

High Flow Hose End Valves

Features: Y-Pattern, Increased Flow over Globe Valve • Light, but Rugged • Use 1-3/4" ACME or 2-1/4" ACME Filler Couplings with no adapters needed • Field Serviceable • 1/4" Recessed Plugs for flow in either direction . Sold as valve only or as complete valve assembly with valve, filler coupling and bleeder assembled.

Not Assorted



Part No.	Description	
ST A330	1-1/4" x 1" Valve ON	LY
ST A331	1-1/4" x 1-1/4" Valve	ONLY
ST A334	1-1/2" x 1-1/2" Valve	ONLY *
ST A1525	1-1/4" x 1-3/4" Fema	lle Acme Hose End Assembly
ST A1527	1-1/4" x 2-1/4" Fema	lle Acme Hose End Assembly
ST A1528	1-1/4" x 2-1/4" Fema	lle Acme Hose End Assembly *
ST A1529	1-1/2" x 2-1/4" Fema	lle Acme Hose End Assembly *
* Liahtweiaht	Aluminum Body.	
3		5% Discount on 10+ Of One Size

NH3 Nurse Tank Valves 1-1/2" & 1-1/4"

For Liquid or Vapor Service

All Valves Include built in excess flow check at GPM noted and hydrostatic relief valve.



Part No.	Description
ST A484N-45	1-1/4" MPT x 1-1/4" FPT NH3 Liquid Valve, 45 GPM
ST A480N-45	1-1/2" MPT x 1-1/4" FPT NH3 Liquid Valve, 45 GPM
ST A480N-60	1-1/2" MPT x 1-1/4" FPT NH3 Liquid Valve, 60 GPM
ST A482N-45	1-1/2" MPT x 1-1/2" FPT NH3 Liquid Valve, 45 GPM
ST A482N-60	1-1/2" MPT x 1-1/2" FPT NH3 Liquid Valve, 60 GPM

Tank Service Valves






AL407EP Service Valves for NH3 liquid or vapor designed for small applicator tanks with 1/2" FPT openings. An excess flow check assembly (12 GPM) is installed in the 3/4" inlet connection for protection in the event of accidental breakage. A 1/4" FPT opening is provided for the installation of a bleeder or hydrostatic relief valve, if desired. Construction consists of steel body, cadmium plated, Teflon stem packing, and long lasting nylon seat. Liquid withdrawal rate - 20 GPM -NH3 @ 20 psi.

EXCESS FLOW CHECK

AL409P designed for liquid withdrawal service in small applicator tanks. The port through the seat is restricted in diameter in accordance with ANSI standards. A 1/4' FPT opening is provided for the installation of any desired accessory. Liquid withdrawal rate - 28 GPM - NH3 @ 20 psi.





- Discounts Not Assorted -

3/4" FPT

0

3/4" MPT

3/8" FPT