

740 Control Valve For Power operated Grease Guns



No. 740

8000 PSI Maximum Pressure

- Precision-machined, all steel handle, body and guard bracket provides durability and longevity.
- Unique precision control inlet check valve provides ease of handle operation even with increase in pressure.
- Knurled handle for positive grip.
- Handy trigger guard prevents pinching.
- Reversible inlet check seat and hydraulic jaws provide double life.
- Balanced design reduces user fatigue.
- Lubricant inlet 1/4" NPT female. Outlet 1/8" NPT female.
- High Pressure - Maximum operating pressure 8,000 psi.

Hydraulic Couplers



No. 25

Heavy-Duty 3 Jaw Hydraulic Coupler with Ball Check. 1/8" NPT (F).



No. 28

Standard 3 Jaw Hydraulic Coupler with Ball Check. 1/8" NPT (F).

Adapter Tube



No. 55

18"NPT (M) both ends. Approximately 5-1/2 long with 15" bend.

Loader Nipple



No. 80

1/8" NPT (a) for filling from gun filler pump. Fits most grease guns.

Coupler Adapter



No. 5848

- 7000 PSI maximum operating pressure.
- Built in swivel-allows full 360 degree circle.
- Versatile-locks in any one of eight 45 degree positions.
- Adjustable coupler section-permits contact with fittings in reverse position.
- Angle body has 1/8" NPT female inlet-permits addition of pipe extension when required.

Extension Adapters



No. 5859 Angle Lube Adapter

- 90 degree angle solves the problem of contacting so-called "inaccessible" grease fittings.
- Unique design eliminates need to remove front "deep dish" wheels for lubrication of the tie rod ends and ball joints.
- Unlimited applications-use to service cars, trucks, machines and farm equipment.



No. 22 Needle Nozzle


Needle design allows operator to contact flush type or hard to reach hydraulic type fittings. 1/8" NPT (F) Needle only is 1/8" x 1-1/2" long



No. 5855 Recessed Lube Adapter

- Straight extension-use to lubricate recessed fittings where obstructions will not permit use of hydraulic coupler. Includes extension nozzle and locking sleeve.

High Pressure Swivels



No. 81387

5000 PSI High Volume

Threads:

1/2"-27 Taper Thd. x 1/4" MPT



Packaged Grease Fittings



10 Fittings Per Card

Pkg. No.	Fitting	Thread
5191	Straight	1/4"-28 short taper
5291	45° Angle	1/4"-28 short taper
5190	Straight	1/8" NPT
5290	45° Angle	1/8" NPT
5490	90° Angle	1/8" NPT

5469 Fitting Assortment



100 assorted grease fittings in six popular sizes. Sturdy, easy to handle transparent dispenser box has labeled and illustrated compartment.

Quantity	Fitting	Thread
20	Straight	1/8" NPT
40	Straight	1/4"-28 short taper
10	45° Angle	1/4"-28 short taper
10	65° Angle	1/8" NPT
10	90° Angle	1/8" NPT
10	90° Angle	1/4"-28 short taper

5470 Fitting Assortment



24 assorted grease fittings in six popular sizes blister packed on one card.

Quantity	Fitting	Thread
6	Straight	1/8" NPT
6	Straight	1/4"-28 short taper
3	45° Angle	1/8" NPT
3	65° Angle	1/4"-28 short taper
3	90° Angle	1/8" NPT
3	90° Angle	1/4"-28 short taper

Part No.

LI 5190	Straight Fitting, 1/8" NPT	(Pkg./10)
LI 5191	Straight Fitting, 1/4"-28 short thread	(Pkg./10)
LI 5290	45° Angle Fitting, 1/8" NPT	(Pkg./10)
LI 5291	45° Angle Fitting, 1/4"-28 short thread	(Pkg./10)
LI 5469	Fitting Assortment (100 pieces)	
LI 5470	Fitting Assortment (24 pieces)	
LI 5490	90° Angle Fitting, 1/8" NPT.....	(Pkg./10)

Lightweight Air Coupler and Nipples



No. 5862 Coupler

250 PSI maximum operating pressure. 1/4" NPT female inlet. Maximum air flow 48 scfm at 100 psi. Length 1-11/16" (43mm); diameter 1-1/8" (29mm); weight 3-1/3 oz.



No. 13329 Nipple
1/4" NPT male.



No. 13331 Nipple
1/4" NPT female.

Part No.

LI 5862	Coupler
LI 13329	Nipple, MPT..
LI 13331	Nipple, FPT ..

Heavy Duty Air Couplers and Nipples



No. 815 Coupler

250 PSI maximum operating pressure. 1/4" NPT female inlet. Extra-long stem of nipple and coupler body assures long service life, easy connections under severe operating conditions. Maximum air flow 52 scfm at 100 psi. Length 2-1/2" (65mm); diameter 1-7/16" (37mm); weight 4-1/2 oz. (126g.).



No. 11659 Nipple
1/4" NPT male.



No. 11661 Nipple
1/4" NPT female.

Part No.

LI 815	Coupler
LI 11659	Nipple, MPT..
LI 11661	Nipple, FPT..

No. 5900 Power Lock Quick Coupler



- 6,000 PSI Maximum Operating Pressure
- For All Hydraulic Grease Fittings
- Built In Ball Check Prevents Leaks



Part No.

LI 740	Control Valve
NS 25	Hydraulic Coupler, Heavy Duty
NS 28	Hydraulic Coupler
NS 55	Adapter Tube
NS 80	Loader Nipple
LI 5848	Coupler Adapter
LI 5859	Angle Lube Adapter
NS 22	Needle Nozzle
LI 5855	Recessed Lube Adapter
LI 81387	Swivel, High Pressure 1/2"-27 x 1/4" MPT ..
LI 5900	Power Lock Quick Coupler, 1/8".....