

## Husky Eagle Flex Series Softwall Gasoline Curb Pump Hose Assemblies



- High Quality Softwall Curb Pump Hose Assemblies; U.L. 330 Listed
- Multiple Textile Spiral Reinforcement for Increased Strength
- Tough Hypalon Cover is Highly Resistant to Cuts, Abrasion, Sun & Weather and Will Not Scratch or Mark Vehicle Finish
- Use with Unleaded & Leaded Gasoline, Diesel, E15 Ethanol & B20
- -40° to 180° F; 150 PSI W.P.
- Permanent MPT Crimped Couplings
- Not for AV Gas

- Custom Lengths Available - Call for Pricing -

Part No.	Hose I.D.	MPT Fittings	Length	Bend Radius
GD L44-3/4X10	3/4"	3/4" MPT	10'	6"
GD L44-3/4X12	3/4"	3/4" MPT	12'	6"
GD L44-3/4X14	3/4"	3/4" MPT	14'	6"
GD L44-3/4X16	3/4"	3/4" MPT	16'	6"
GD L44-3/4X20	3/4"	3/4" MPT	20'	6"
GD L44-1X12	1"	1" MPT	12'	8"
GD L44-1X14	1"	1" MPT	14'	8"
GD L44-1X16	1"	1" MPT	16'	8"
GD L44-1X20	1"	1" MPT	20'	8"

Less 10% On 5 or More of One Size



## Husky EagleFlex® Farm Pump Hose Assemblies



**Features:** Suitable for gasoline, diesel fuel and oil • Abrasion-resistant & designed for durability and flexibility • Tube: Nitrile Buna Rubber (NBR) • Cover: Nitrile Buna Rubber (NBR)/PVC • Helical-reinforced: Spiral high-tensile strength polyester cord • Temperature Rating: -20° F. to 160° F. • Maximum Working Pressure is 60 PSI • Stainless Steel Ferrule/Zinc Stem, Permanent External Fixed Couplings • Supplied with static wire – all assemblies are 100% inspected for electrical continuity • Static wire hoses are recommended for use with electrical pumps • **DO NOT USE** these hoses at service station or to refuel aircraft.

Part No.	Length	I.D.	Couplings
GD L64-3/4X10	10'	3/4"	3/4" MPT
HK FT12S14	14'	3/4"	3/4" MPT
HK FT12S20	20'	3/4"	3/4" MPT
GD L64-1X10	10'	1"	1" MPT
GD L64-1x12	12'	1"	1" MPT
HK FT16S14	14'	1"	1" MPT
HK FT16S20	20'	1"	1" MPT

Less 10% On Standard Pkgs.

Custom Lengths Available Call for Pricing



## OIL SHIELD® Fuel Transfer Hoses

For Use with Gasoline, Diesel, Kerosene, Ethanol, Bio Diesel B10 & B20 Formulations

**FEATURES:** Ozone & abrasion-resistant cover • Two times the kink resistant of other fuel hoses • Class A oil-resistant tube & cover • Rated to 100 PSI • 8" Internal strain relief spring • Cold weather rated, Flexible to -30° F. • Male MPT fittings • 1 Year warranty • Static wire rated for use with electric pumps where UL approval "Is Not" required.



Part No.	I.D.	Length	* Std. Pack	Wt. Lbs.
RX OSFH3410	3/4"	10'	4	4
RX OSFH3412	3/4"	12'	4	5
RX OSFH3414	3/4"	14'	4	6
RX OSFH3420	3/4"	20'	4	8
RX OSFH3430	3/4"	30'	-	12
RX OSFHONE10	1"	10'	4	5
RX OSFHONE12	1"	12'	4	6
RX OSFHONE14	1"	14'	4	7
RX OSFHONE20	1"	20'	3	10
RX OSFHONE30	1"	30'	-	15

\* 5% Discount for Standard Pack Purchase

## Husky Eagle Flex Series Hardwall Gasoline Curb Pump Hose Assemblies



- High Quality Hardwall Curb Pump Hose Assemblies; U.L. 330 Listed
- Wire Braid Reinforcement Provides Strength, Resistance to Crushing, Kinking & Tight Bend Radius
- Tough Hypalon Cover is Highly Resistant to Cuts, Abrasion, Sun & Weather and Will Not Scratch or Mark Vehicle Finish
- Use with Unleaded & Leaded Gasoline, Diesel, E15 Ethanol & B20
- -40° to 180° F; 150 PSI W.P.
- Permanent MPT Crimped Couplings
- Not for AV Gas



- Custom Lengths Available - Call for Pricing -

Part No.	Hose I.D.	MPT Fittings	Length	Bend Radius
PA 7124-3/4X9	3/4"	3/4" MPT	9'	4"
PA 7124-3/4X10	3/4"	3/4" MPT	10'	4"
PA 7124-3/4X12	3/4"	3/4" MPT	12'	4"
PA 7124-1X9	1"	1" MPT	9'	5"
PA 7124-1X12	1"	1" MPT	12'	5"
PA 7124-1X20	1"	1" MPT	20'	5"

Less 10% On 5 or More of One Size



## Bulk Curb Pump Hose

NOT FOR BIODIESEL or AV GAS

Part No.	I.D.	O.D.		Wt. Per 100'
GD CP12SW	3/4"	1.125"	2-Braid Softwall Hose	35 lbs.
GD CP16WB	1"	1.375"	1-Wire Braid Hose	49 lbs.

Less 20% On 100'

## Hose End Couplings



**Reusable Chrome-Plated Brass Hose End Couplings** simplify fitting hose. A sturdy wrench and vice complete the job quickly and easily with long life and smooth connections. **Important to check for continuity after installation.**

Part No.	MPT	Hose I.D.	Fits Hose O.D.
GD CP12R73	3/4"	3/4"	1-1/8"
CB 8508-4-1	1"	1"	1-3/8"
CB 8508-1-1	1"	1"	1-1/2"

## Super Safe-T-Break Valves

Protects Against Dangerous Runaway Fuel Spillage  
Reusable Model



**Super Safe-T-Break Coupling** prevents fuel spillage if car pulls out with nozzle still in tank! This fitting attaches to the short fuel hose (shown) and breaks away when pull reaches a maximum of 200 pounds pressure. Butterfly check valves immediately close, preventing runaway fuel spillage from both sides of valve. **Reusable model.** Hoses are U.L. listed, hardwall.

**Note:** Safe-T-Break must be installed downstream (at nozzle end) of any hose with retractor cable.

Part No.	Size	
HK 3360	3/4"	Safe-T-Break Valve .....
GD CP12AH75	3/4"	3/4"x9" Breakaway Hose, Non Swive.....
HK 2276	1"	Safe-T Break Valve.....
GD CP16AH75	1"	1"x9" Breakaway Hose, Non Swivel.....

Please remember there are No Returns on customer specified cut lengths of hose.