

**Carbonator Pump Motors**

Designed for close-coupled pump applications. Ideal for compact pump/motor applications. Slotted 5/8" shafts are designed to accept flat-shaft pumps such as Procon or Rotoflow brands.

**Features:** 1-Phase, Open-Dripproof • 1725 RPM • Rated for continuous duty • Automatic overload protection • Frames are 48YZ • Rotation can easily be changed in the field if required.

Part No.	Size	Voltage	Amp Rating	Wt.
CE 931	1/3 HP	115	5.6	16 lbs.
CE 932	1/2 HP	115/230	7.2/3.6	19 lbs.
CE 933	3/4 HP	115/230	10.4/5.2	25 lbs.



Slotted Shaft

**Ground Fault Circuit Interrupter**

For indoor or Outdoor Use.



GFI power cord is UL listed and features Test Button, Reset Button and Power-On indicator light. 25ft cord has 3-prong plug on one end and blunt cut 3 wires on other end for direct wiring to existing motors. 12 gauge, 20amp rating.

Part No.	Length	Rating	Gauge
DU 1051-12-25	25'	20amp	12

Visit our office in Omaha, Nebraska



13808 Industrial Road • Omaha, NE 68137  
1-800-228-9666 • 1-402-333-1444 • FAX: 1-402-333-5546

Visit our office in Davenport, Iowa



601 West 76th St. • Davenport, IA 52806  
1-800-553-6975 • 1-563-386-0930 • FAX: 1-563-386-5448

email: dultmeier@dultmeier.com • website: dultmeier.com

*thank you!*

WE APPRECIATE YOUR BUSINESS

**Hour Meters**



Compact, top quality elapsed time indicators for implementing an efficient preventive maintenance program on your pumps or equipment.

These hour meters are available in 24 Volt or 120 Volt and in resettable and non-resettable models. Counter wheels have large, easy-to-read numbers. Whole numbers are white against black background. Decimal number is black on white background.

High impact housing with round or square faces. All models include 6" wire leads. All models are UL listed.

**2PAT4:** 115 Volt push button **resettable** meter. Registers elapsed time up to 9999.9 hours. 2-1/2" face.


**2PAT3:** 115 Volt **non-resettable** meter. Registers elapsed time up to 99999.9 hours. 2-1/2" bezel face. Length is 2-3/4" front to back.

**3410-1000:** 24 Volt non-resettable meter. Registers elapsed time up to 99999.9 hours. 2-13/16" round bezel face. Length is 2-3/4" front to back.

Part No.		Voltage
GN 2PAT4	Resettable Meter .....	120
GN 2PAT3	Non-Resettable Meter..	120
NP 3410-1000	Non-Resettable Meter..	24

**Adjustable Steel Motor Bases**

Simplify Mounting and Belt Tension Adjustment



One-piece steel mounting bases have single adjusting bolt to position mounted motor for proper belt tension during initial installation and at later maintenance checks. Four motor mounting bolts included. Not for ceiling or sidewall installations. Gray finish.

Part No.	FOR NEMA		Wide	Long	Bolt Size
	FRAME NO.'S				
GN 3M276	56		6-1/2"	10-5/8"	5/16"
GN 3M277	143T		7-1/2"	10-1/2"	5/16"
GN 3M278	145T		8-1/2"	10-1/2"	5/16"
GN 3M279	182T/182		9-1/2"	12-3/4"	3/8"
GN 3M280	184T/184		10-1/2"	12-3/4"	3/8"
GN 3M281	213T, 213		11"	15"	3/8"
GN 3M282	215T, 215		12-1/2"	15"	3/8"
GN 2M512	254T		15-1/8"	17-3/4"	1/2"
GN 2M513	256T		16-7/8"	17-3/4"	1/2"
GN 2M514	284T		16-7/8"	19-3/4"	1/2"
GN 2M515	286T		18-3/8"	19-3/4"	1/2"
GN 2M516	324T		19-1/4"	22-3/4"	5/8"

**Power Cords**

Plug with Bare Cord Ends




1FD92



1FD93

Part No.	Gauge	Wires	Length	Grounded	Ends
GN 1FD92	14	3	8'	Yes	Bare
GN 1FD93	12	3	8'	Yes	Bare

**Pressure Switch Controls**



**Furnas Pressure Controls** are the first choice for contractors, industrial users and others for air compressor applications and water systems. 1/2" conduit openings and ample wiring space, black finish. Lower female 1/4" MPT connection. U.L. listed.

Part No.	PSI Range	Adjusted Diff. PSI Min Max.	Factory Set PSI On/Off	RATING IN HP		
				Single Phase AC	Three Phase AC	240-V
GN 3X681	20-100	20 to 60	80/100	1-1/2	2	3
GO 69WR7	35-150	30 to 45	95/125	1-1/2	2	3
GN 3X683†	35-150	30 to 45	95/125	1-1/2	2	3

† Model 3X683 Has Built-in Unloader Valve to reduce starting Load.

Part No. GN 3X681 GO 69WR7 GN 3X683