


Ball Bearing Swivels

Completely Rebuildable
Pressures to 3500 PSI

High Pressure Swivel with brass body and stainless steel thrust bearings. Internally lubricated o-rings and 303 stainless center spool piece assure long trouble-free operation. Pressures to 3500 PSI. Maximum temperature is 160° F.



Part No.	Pipe Thread Ports	Const.	Max. PSI
FL SW504	1/4" MPT x 1/4" FPT	Brass	2000
FL SW504A	3/8" MPT x 3/8" FPT	Brass	2000
FL SW504HP	1/4" MPT x 1/4" FPT	Brass	3500
FL SW504AHP	3/8" MPT x 3/8" FPT	Brass	3500
FL RK550	Repair Kit for Swivels Above		



Wand Swivels

Easy turn gun swivels for high pressure spray wands. High quality, Swiss-Made, construction. Rated to 4000 PSI & 250° F. Nickel-plated brass body, stainless steel bearing. Available in 1/4" and 3/8" sizes in male thread, (MPT) and female thread, (FPT). Nitrile o-ring.



Part No.	Ports	Max. PSI
MM 32569	3/8" FPT x 3/8" FPT	4000
MM 32564	3/8" MPT x 3/8" FPT	4000
MM 32563	3/8" MPT x 3/8" MPT	4000
MM 32562	3/8" MPT x 1/4" FPT	4000
MM 32561	3/8" MPT x 1/4" MPT	4000
MM 32557	1/4" FPT x 1/4" FPT	4000
MM 32552	1/4" MPT x 1/4" FPT	4000
MM 32863	*1/2" MPT x 1/2" MPT	4000
MM 32864	*1/2" MPT x 1/2" FPT	4000

**CALL
for
PRICING**

* High Flow Swivels



Hydraulic Fluid Swivels

High Pressure, Hydraulic "Live" Swivels are available in either "Inline" or "90° angle" styles. Designed for the rigors of hydraulic fluid requirements. Chrome ball bearing design for added life. Easily rebuildable. Superior quality alloy steel. All swivels shown are "inline" design except for 9SS models.

Rated to 5000 PSI. Retrofits to brands such as *Parker Hannifin, Aeroquip, Hydraulics Inc.*, etc. Zinc-plated Carbon steel construction with Viton® seals are standard. Maximum temperature: -15° F. to +250° F.

Part No.	Inlet Port	Outlet Port
SE SS614	1/4" FPT	1/4" FPT
SE SS614MF	1/4" MPT	1/4" FPT
SE SS838	3/8" FPT	3/8" FPT
SE SS838MF	3/8" MPT	3/8" FPT
SE SS812	1/2" FPT	1/2" FPT
SE SS812MF	1/2" MPT	1/2" FPT
SE SS1234V	3/4" FPT	3/4" FPT
SE SS1234MFV	3/4" MPT	3/4" FPT
SE 16015V	1" FPT	1" FPT
SE 9SS83CV	* 3/8" FPT	3/8" FPT
SE 9SS81CV	* 1/2" FPT	1/2" FPT
SE SS8KIT	Repair Kit, 3/8" & 1/2"	
SE 20183	Repair Kit, 3/4"	
SE SS16KIT	Repair Kit, 1"	

* 90 degree design.



Inline Swivel



90° Swivel

SUTTNER Swivels

High Pressure Swivels from Suttner! Available in 3/8" MPT x FPT or 3/8" FPT x FPT. Rated to 5000 PSI. Maximum temperatures to 300° F. Rated to 12 GPM. Nickel-plated brass or stainless construction. Rebuildable design. Teflon seal.

Part No.	Ports	Type
NP ST300	3/8" M x F	Brass
NP ST325	3/8" F x F	Brass
NP ST310	3/8" M x F	Stainless
NP ST300K	Repair Kit	



High Pressure Inline Swivels



FPT Swivel MPT Swivel

Super Swivels "Inline Swivels" are designed with AFLAS™ seals for water, soap or wax solutions (*Viton® also available*). Rated for pressures up to 3,000 psi. Maximum temperature: +32° F. to +400° F. Available in zinc-plated carbon or stainless steel high quality alloy steel. Easily rebuildable. "Live" design swivels under pressure. (*For Hydraulic fluids - See Hydraulic swivels shown elsewhere on this page.*)

Part No.	Construction	Inlet Port	Outlet Port
SE SS838-A	Plated	3/8" FPT	3/8" FPT
SE SS838MF-A	Plated	3/8" MPT	3/8" FPT
SE SS812-A	Plated	1/2" FPT	1/2" FPT
SE 14090	* Plated	1/2" FPT	1/2" FPT
SE SS812MF-A	Plated	1/2" MPT	1/2" FPT
SE SS1234	Plated	3/4" FPT	3/4" FPT
SE SS1234MF	Plated	3/4" MPT	3/4" FPT
SE 16015	* Plated	1" FPT	1" FPT
SE 1244	Plated	1" MPT	1" FPT
SE 1046	Stainless	1" FPT	1" FPT
SE SS20AL	Plated	1-1/4" FPT	1-1/4" FPT
SE SS20MF	Plated	1-1/4" MPT	1-1/4" FPT
SE 1064	Plated	1-1/2" FPT	1-1/2" FPT
SE 1264	Plated	1-1/2" MPT	1-1/2" FPT
SE SS8KIT-AL	Repair Kit, 1/2" Swivels		
SE 20183	Repair Kit, 3/4" Swivels		
SE SS16KIT-AL	Repair Kit, 1" Swivels		
SE SS20KIT-AL	Repair Kit, 1-1/4" Swivels		

* Double Bearing Design.

High Pressure Swivels

For pressures to 3000 PSI. Stainless Steel or brass construction. Bearings are self-lubricated Teflon filled acetal for long life and low torque requirements. Maximum temperature is 200° F. Ports are 3/8" FPT x 3/8" MPT.



Part No.	3/8" MPT x 3/8" FPT SWIVEL	Max. PSI
SS 15950SS	Stainless Steel construction	3000
SS 15950B	Brass construction	3000
SS AB15950	Repair Kit	

Medium Pressure Swivels


Ideal for guns and pumping systems up to 1000 PSI. No Ball Bearings to gall or rust. All Brass Body. Available in 1/4", 3/8" and 1/2" sizes. Non-repairable. Maximum Temperature is 180° F.



Part No.	Pipe Thread Ports	Max. PSI
SM 902-1/4	1/4" MPT x 1/4" FPT	1000
SM 900-3/8	3/8" FPT X 3/8" MPT	1000
SM 901-1/2	1/2" FPT x 1/2" MPT	1000

Dual Nozzle Selector

Dual Nozzle Selector from *Cat Pumps®*. Designed for use with two spray nozzles for high and low pressure. Dual nozzle selector enables the operator to use a downstream injector for corrosive chemical injection. Simple right to left turn rotates ball to open high or low pressure passage. Maximum flow is 7 GPM, Maximum pressure is 3000 PSI. Inlet port is 1/4" FPT. Nozzle ports are 1/4" FPT.



Part No.
CC 32149



Viton® is a registered trademark of DuPont Performance Elastomers