

FILL-RITE Remote Mount Pumps

For flexible and convenient applications on Above Ground Storage Tanks, combine these Remote Mount Pumps with the Remote Dispensers shown below.

Standard Features:

- Rain-Proof Cast Iron Pump Housing: Iron Motor
- Explosion-Proof UL/cUL Listed Motors
- Motors have Sealed Bearings, Heavy-Duty Switch and Thermal Overload Protection
- Built-In Junction Box
- Integral Check Valve, Pressure Relief Valve and Strainer Assembly (*No foot Valve Required*)
- Automatic Bypass Valve, Anti-Siphon Device, Tank Adapter, Fittings and Anti-Siphon Pipe
- 2" MPT Base to Fit Standard Tank Openings
- 115 Volt Motors Standard - 220 Volt is Available
- Conversion Kits Available for B20-B100 Biodiesel & E-85 Ethanol

Part No.		Wt.
FR FR713	1/3 HP, 115V Remote Pump ONLY for gasoline or diesel (15-18 GPM).....	43 lbs.
FR NX25-120NB-PX	Fuel Pump ONLY NX25, 120V.....	22 lbs.
FR 313	3/4 HP, 115V Remote Pump ONLY for diesel (30 GPM).....	68 lbs.
DU 1-1/4X48	1-1/4" x 48" Suction Pipe	-
DU 1-1/4X63	1-1/4" x 63" Suction Pipe	-

(See Remote Dispenser Units Below)



FR713



FR313

FILL-RITE Remote Mount Dispensers



902CRU

Use with Remote Mount Pumps above in Above Ground Storage Tank applications for convenient access to meter and nozzle. Units include 901 1" Series meter and nozzle "boot", 1" opening and 1" rear discharge (*front discharge available*) and solenoid valve. **Hose and nozzle are not included.** Flow rates from 6 to 40 GPM.

902DPU is a digital version and includes pulse output, solenoid valve and water hammer arrestor. 2" Inlet and 1" outlet. 115 Volt. **U.L. Listed in U.S. and Canada.**



902DPU

Part No.		Wt.
FR 902CRU	Single Product Remote Dispenser System, UL Listed (US & Canada).....	49 lbs.
FR 902DPU	Digital Version of Above Dispenser System....	108 lbs.
FR KITWM	Optional Wall Mount Bracket for Both.....	-
FR KITPD	Optional Pedestal Mount Kit for Both.....	-

FILL-RITE Compact Cabinet Pump Units for Above Ground Storage Tanks

These "Cabinet" Style Pump/Meter Units are specifically designed for Above Ground Storage Tanks (AST's)

Standard Features:

- Rain-Proof Cabinet includes Pump & Meter - 18 GPM
- 1/3 HP Explosion-Proof UL/cUL Listed Motors
- Motors have Heavy-Duty Switch, Thermal Overload & Junction Box
- 800C Meter with Mechanical Totalizer
- Integral Check Valve (*No foot Valve Required*)
- 3/4" x 12' Hose, Standard Manual Nozzle (*Automatic Nozzle available*), Standard Nozzle Boot, Rear Discharge
- 2" MPT Base to Fit Standard Tank Openings
- 115 Volt Motors Standard; 220 Volt Available
- Conversion Kits Available for B20-B100 Biodiesel & E-85 Ethanol and Vapor Recovery Model

Part No.		Wt.
FR FR702R	1/3 HP, 115V Cabinet Pump System	72 lbs.
DU 1-1/4X48	1-1/4" x 48" Suction Pipe	-
DU 1-1/4X63	1-1/4" x 63" Suction Pipe	-



FR702R