



Bulk Wash Down Hose Smooth Cover

Clean Master Wash Down Hose from Gates is designed for hot water and cold water pressure cleaning in car/truck wash, pressure wash, carpet cleaning, industrial cleaning, food processing and other applications where heavy-duty service is required. Special compound smooth cover is abrasion and ozone resistant. Available in black, blue and gray. Blue and gray hose is "non-marking". Available in 1 or 2 wire construction as shown. Rated from -40° to +250°F. Sold by the foot cut to length in 5' increments or in 300' reels. Can be used with crimp or reusable fittings. **(Note: All reels have a maximum of 3 pieces none shorter than 50' except 8BL-3/8 which is a 300' continuous length).**



Clean Master



NOTE: CUT LENGTHS SOLD IN 5' INCREMENTS ONLY


Part No.	Pressure	Hose Type	I.D.	O.D.	* Std Pkg.
GA PC-1/4	4000 PSI	Black, 1-Wire	1/4"	.53"	300'
GA PC-3/8	4000 PSI	Black, 1-Wire	3/8"	.67"	300'
GA PC4-3/8	5000 PSI	Black, 2-Wire	3/8"	.74"	300'
GA PC-1/2	3000 PSI	Black, 1-Wire	1/2"	.79"	300'
GA 6BL-1/4	4000 PSI	Blue, 1-Wire	1/4"	.53"	300'
GA 6BL-3/8	4000 PSI	Blue, 1-Wire	3/8"	.67"	300'
GA 8BL-3/8	*4000 PSI	Blue, 1-Wire	3/8"	.68"	300'
GA 6GY-3/8	4000 PSI	Gray, 1-Wire	3/8"	.67"	300'
GA 6GY-1/2	4000 PSI	Gray, 1-Wire	1/2"	.80"	300'

* Imported, Not Gates Brand, Features Continuous Length for this Part Only.

*** 10% Discount for Standard Pack Purchase**

T136 Hot Water Washdown Hose

An ideal choice for plant wash down or automatic car wash applications. Rated to 1000 PSI constant pressure. I.D. Maximum temperatures to 200° F. Cover is Yellow SBR/NBR blend that is abrasion, ozone, hydrocarbon and fire resistant - pin pricked. High tensile braided steel wire reinforcement. Tube is black extruded SBR/NBR blend - oil mist resistant. **T136** specifications. **Note: We can supply 3/4" and 1", 50ft. and 100ft. coupled hose assemblies with GLX hydraulic fittings. If field assembled, you must use GLX or Bandit clamp connections. Do Not Use worm drive clamps.**



1,000 PSI

Part No.	I.D.	O.D.	Std. Pkg.	Wt. Per Pkg.
TF T136A7-075X50	3/4"	1.10"	50	22 lbs.
TF T136A7	3/4"	1.10"	100	44 lbs.
TF T136A10-100X50	1"	1.34"	50	29 lbs.
TF T136A10	1"	1.34"	100	58 lbs.
TF T136AK150	1-1/2"	1.93"	50	54 lbs.
TF T136AK-150X100	1-1/2"	1.93"	100	108 lbs.
TF T136AK200	2"	2.48"	50	74 lbs.
TF T136AK-200X100	2"	2.48"	100	148 lbs.

Standard Package Only - All Sizes - No Cuts.



Steam Hose



7263

PARKER Steam Hose for long lasting service with saturated and superheated steam. EPDM tube and wire braid reinforcement for crush resistant durability, kink resistance and static electrical charge to ground.

Black EPDM cover is resistant to abrasion, cracking, hardening and ozone. Rated from -20° F. to +406° F. with saturated steam and +450° F. with superheated steam. Maximum 250 PSI. *** Some sizes sold by the foot - others require full RL purchase. Those sold by the foot are sold in 5ft minimum increments. Use with Dixon Boss fittings for assembly in the field.**

Part No.	I.D.	Couplings	Wts. Per Foot
PA 7263-752	3/4"	Dixon Boss	.66 lbs
PA 7263-1002	1"	Dixon Boss	.85 lbs
PA 7263E-1502*	1-1/2"	Dixon Boss	1.44 lbs
PA 7263E-2002*	2"	Dixon Boss	1.76 lbs

*** Full RL Only**

Fitted Steam Hoses



Fitted Steam Hoses for use with steam cleaning applications or high pressure, hot water. Rated to 350° F. for steam @ 350 PSI, (250° F. @ 3000 PSI for 3/8" or 2500 PSI for 1/2"). Solid MPT ends with bend restrictors are standard. Black, 1-wire rubber construction.

Part No.	Size	Wt.
GA A4300-3850	3/8" x 50'	14 lbs.
GA A4300-38100	3/8" x 100'	26 lbs.
GA A4300-1250	1/2" x 100'	17 lbs.
GA A4300-12100	1/2" x 100'	32 lbs.

Bulk Wash Down Hose Wrapped Cover

Wrapped Cover Hose offers superior wear resistance to smooth rubber hose. Great choice for hot or cold water cleaning applications. Oil resistant tube and cover. One or two wire construction in 1/4", 3/8" and 1/2" I.D. Can be crimped on site with permanent or reusable fittings matched to hose O.D. Quantity discount for full reel purchases. Rated to 250° F.

1SN & 2SN



1SN (1Wire) and 2SN (2Wire) Series hose feature a standard "wrapped" cover for added performance and wear life compared to smooth cover hose.

5RM



5RM (2 Wire) Series hose features a standard "wrapped" cover but with the addition of a "polyethylene coating" that is impregnated into the cover. This gives maximum wear and abrasion resistance compared to any other wrapped or smooth cover rubber hoses.

Highest Abrasion Resistance

Part No.		I.D.	O.D.	Max. PSI	* Std. Pkg.
GA 1SN-1/4	Black Wrapped, 1-Wire	1/4"	.48"	3250	800'
GA 1SN-3/8	Black Wrapped, 1-Wire	3/8"	.65"	4000	300'
GA 2SN-3/8	Black Wrapped, 2-Wire	3/8"	.70"	6000	300'
GA 2SN-1/2	Black Wrapped, 2-Wire	1/2"	.84"	4000	250'
GA 5RM-3/8	Black Wrapped with Poly, 2-Wire	3/8"	.72"	5500	500'
GA 5RM-1/2	Black Wrapped with Poly, 2-Wire	1/2"	.84"	4300	250'

*** 10% Discount if ordered in Standard Pack Reels. Reel Lengths are Approximate and May Vary. Non Continuous Lengths, May be Up to 3 lengths Per Reel with No Length Less than 50 Ft.**



Hurricane Pressure Washer Hose Wrapped Cover - 1 Wire

Bulk Pressure Washer Hose from Parker. Ideal for use with hot or cold water pressure washers in plant wash down or car/truck wash applications. **Made in the USA.**

Single wire, wrapped cover hose rated to 3,000 PSI. Available with either standard black or non-marking blue covers. Tube and cover are Neoprene construction. Temperature ratings from -40° to +250° F. We can assemble hoses to meet your specifications. **Note: Cut Lengths Sold in 5' Increments Only.**

Note: Not intended for carpet cleaning applications!



Part No.		I.D.	O.D.	Max. PSI	Std. Pkg.
PA 7258-1/4	Black Hose, Bulk	1/4"	.500"	3000	500'
PA 7258-3/8	Black Hose, Bulk	3/8"	.625"	3000	500'
PA 7258-3/8B	Blue Hose, Bulk	3/8"	.625"	3000	500'

*** 10% Discount if ordered in Standard Pack Reels. Reel Lengths May be Up to 3 lengths Per Reel with No Size Less than 50 Ft.**




Alfagomma Steam Hose



Kuriyama

The Alfagomma T340 Series from Kuriyama is a general steam transfer hose that is rated up to 270PSI and 410°F. Designed for transfer of saturated steam. This hose series has a black (available in red T340AH) EPDM heat-resistant, wrapped cover. The cover is pin-pricked to allow for venting. Not recommended for washdown applications where detergents or oils are present. General use steam hose used in superheated steam will shorten hose life. For superheated steam applications, see T341 (Chlorobutyl) Series. Proper draining after each use will increase service life. Available in Black/Red Covers for both T340 and T341 Series. Not all sizes/covering options shown - Call for Details. Factory Premade Assemblies Available - Call for Details.



Working Pressure: 270PSI Max

Temperature: 410°F Max

Cover: Heat-resistant EPDM, Pin-Pricked

Tube: Extruded heat resistant EPDM (T340)/heat-resistant Chlorobutyl (T341)

Reinforcement: Wire Braid

***Not for Steam Cleaner Use**

****WARNING - Handling steam is extremely hazardous. If it is not properly controlled it can cause property damage, injury or even death. Selection for the proper application, usage, and maintenance will not only increase hose life but will ensure safe operation for the user.****

Part No.	Size	Color	Bend Radius	Wire	Discount
TF T340AA-1/2†	1/2"	Black	5"	Single	-
TF T340AA-3/4	3/4"	Black	7-1/2"	Single	25% - 100'
TF T340AA-1	1"	Black	10"	Two	25% - 100'
TF T341AH-1-1/4*†	1-1/4"	Red	12-1/2"	Two	-
TF T341AH-1-1/2*†	1-1/2"	Red	15"	Two	-
TF T340AA-2†	2"	Black	20"	Two	-
TF T340AA-3†	3"	Black	30"	Two	-

* T341 Rated for superheated steam applications (Chlorobutyl Tube)

† Sold in 100' RL Only