

## Hose Swivels

**Features:** Double swivels at each swivel point. • Castings are of new high-strength alloy • Extremely low resistant aerodynamics achieve a near constant velocity with minimum turbulence • Has a smaller, lighter, and even better flow rate • Has full 360 degrees rotation on both planes.



Part No.	Hose Swivels
HK 16-1Mx3/4F	1" MPT x 3/4" FPT
HK 16-3/4Mx3/4F	3/4" MPT x 3/4" FPT

## Husky Hose Swivels




0087



0095

**Husky 0095 & 0087 Swivels** are compact for easy handling and compatible with fuels containing alcohol. These swivels are high flow up to 45 GPM. **No. 0095** is 360° single plane and **No. 0087** is 360° multi-plane.



4860

**Husky No. 4860** is for high flow fueling. Flow rate is to 100 GPM. This swivel is 360° double plane.

Part No.	Size	Flow Rate
HK 0087	1" M x 1" F	45 GPM
HK 0095	1" M x 1" F	45 GPM
HK 4860	1" M x 1" F	100 GPM

## Fuel Hose Swivels



**Aluminum Body - Nitrile O-Ring**  
For Gasoline, Diesel Fuel and Oil Products

Part No.	Size
HK 5235	1-1/4" FPT x 1-1/4" MPT
HK 5240	1-1/4" FPT x 1-1/2" MPT
HK 5265	1-1/2" FPT x 1-1/4" MPT
HK 5266	1-1/2" FPT x 1-1/2" MPT



## 122 Hose Nozzle Swivels

With Viton® O-Rings • 125 PSI



Part No.	MPT x FPT	Material	Wt.
MB 122-1X1	1"	Brass	1
MB 122BH-1-1/4	1-1/4"	Brass	1
MB 122-1-1/2	1-1/2"	Brass	2

## Test Well Cap & Adapter

### CONSTRUCTION DETAILS

**Cap:** Aluminum  
**Adapter:** Brass

Adapter fits SCH-40 PVC Well Screen Pipe  
Inside of Adaptor Serrated  
for Press Fit  
Tamper Proof - Water Tight

178-XA



Part No.	Size	Wt.
MB 178XA-2	Test Well Adapter & Cap	2" 1 lb.

Size	Wt.
2"	1 lb.

Viton® is a registered trademark of DuPont Performance Elastomers

## Fig. 710 Fuel Solenoid Valves

Normally Closed

The **Fig. 710 Solenoid Valve** is a two-way, one direction flow, hung piston valve that is normally closed in the "at rest" position. The valve opens upon receipt of an electronic signal such as when a dispenser or pump is switched on. CSA certified (Non-UL). Standard in forged bronze.



**Features:** Operates at 120 Vac (12, 24, 240 & 480 Volt available) • Includes a continuous duty Class H standard coil • No differential pressure is required to open the valve • Connects to a 1/2" conduit • Enclosure is watertight and rated for hazardous locations - NEMA 3, 4X, 7 and 9; groups C and D • Standard with Viton® seals (Teflon available) • Has a built-in expansion relief • Maximum viscosity rating of 60 Centistokes (20 wt. oil max.) • Must be mounted with solenoid vertical and upright. A strainer with a 100 mesh screen is required at the inlet. Also available in stainless and Teflon for DEF in same sizes.

Part No.	Description
MB 710-0.75V	3/4" Solenoid Valve, Brass.....
MB 710-1V	1" Solenoid Valve, Brass.....
MB 710-1.5V	1-1/2" Solenoid Valve, Brass ...
MB 710-2V	2" Solenoid Valve, Brass.....
MB 710-3V	3" Solenoid Valve, Brass.....

## Fig. 9095A Fuel Overfill Protection Valves

- Adjustable Float
- 100 PSI Rating
- Overfill Protection for Gas, Diesel, E15 & B20
- Cushioned Shut-Off
- Body: Anodized Aluminum
- Internals: Brass/Stainless Steel.
- Linkage: Stainless
- Not for Motor Oils, Waste Oil or Other Heavy Oils



The **Fig. 9095A Overfill Prevention Valve** is installed at the top fill port of an above ground storage tank. Used in a tight fill application, the valve terminates flow of product when the liquid level reaches a preset warning level (90-95% full tank). When installed to manufacturers requirements the Overfill Prevention Valve can eliminate overfill spills. A built-in bleed hole also provides an anti-syphoning protection. Works with aluminum drop tubes or standard steel pipe. U.L.C. listed. Also complies with NFPA30, BOCA, PIE/RP2000.

Part No.	Ports	Maximum Flow	Install On	Net Ea.
MB 9095A-32AV	2"x2"x4" Female Adapter	100 GPM	4" Nipple	CALL for PRICING
MB 9095A-33AV	3"x3"x6" Female Adapter	300 GPM	6" Nipple	CALL for PRICING

## Aluminum Drop Tubes

Part No.	Aluminum Drop Tubes
MB 419-2X4	2" x 4' Aluminum .....
MB 419-2X6	2" x 6' Aluminum .....
MB 419-2X12	2" x 12' Aluminum .....
MB 419-3X12	3" x 12' Aluminum .....
MB 419-4X12	4" x 12' Aluminum .....

**CALL for CURRENT PRICING**