

BANJO Heavy Duty Tank Valves

- Four Variations of 3" Heavy Duty Polypropylene Tank Valves with Stainless Ball Stem, Handle & Bolts.
- Locking Handle with MPT, Part A Adapter or Flange Connections.
- 100 PSI Teflon Seals.
- Viton® Body Seals.
- Use with Heavy Duty Bolted Flange Clamps (shown on adjacent pages)



V700/V800
MPT x Adapter



V701/V801
Flange x Adapter



V803
Flange x Flange



V802
MPT x Flange



Part No.	BANJO Valve
TK V700	2" MPT x 2" A Adapter.....
TK V800	3" MPT x 3" A Adapter.....
TK V802	3" MPT x 3" Flange.....
TK V703	2" Flange x Flange
TK V803	3" Flange x Flange

BANJO Polypropylene Swivels



SW Style

- Teflon Thrust Bearing
- Viton® O-rings
- Heavy Duty Reinforced Polypropylene
- Hex Flats
- S.S. Drive Stud
- 75 PSI



MSW220

Part No.	Description
TK SW100	1" Female x 1" Male Poly Swivel.....
TK SW150	1-1/2" Female x 1-1/2" Male Poly Swivel.....
TK SW200	2" Female x 2" Male Poly Swivel.....
TK MSW220	2" FP Flanged Poly Swivel.....

Easy-Fill™ Valves

These Polypropylene Valves eliminates the need for multiple fittings. The stubby valve design also reduces length. Extended coupler prevents handle interference.



Part No.	Description
TK VSBHB205FP	2" FP EASY-FILL Valve with Carry Handle.
TK VSBHB304FP	3" FP EASY-FILL Valve No Carry Handle...
TK H25053	2"/3" Easy Carry Handle *.....

* Easy Carry Handle works with many other Banjo Valves on Adjacent Pages.

BANJO Manifold Single Union Valve Flange X Flange

- Precision molded in polypropylene. Reinforced with fiberglass.
- PTFE Seats for Smooth Operation & Proper Sealing.
- EPDM O-Rings.
- Interlocking Body & End Plate.
- Double O-Rings in Stem Area.
- 100 PSI rating.



Part No.	Max. PSI	Pipe Size	Opening Thru Ball
TK MSUV100FP	100	1"	1"

2" Full Port ANSI Flange Bolted Poly Ball Valve



- 100% PTFE Seats.
- FKM (Viton®) Seals.
- Glass-Filled Polypropylene.
- Unique Compact Design.
- Lightweight.
- Maximum Operating Pressure is 150 PSI @ 70° F.

Part No.	Max. PSI	Pipe Size	Opening Thru Ball
TK VSF200FPAF	150	2"	2"

Flanged Bolted 5-Way Ball Valve

- FKM (Viton®) Seals.
- PTFE Self-Lubricating Stem Bushings
- Fiberglass-Filled Polypropylene.
- Self-Aligning Ball Valves for Smooth Operation.
- Ball is Diamond Turned
- Maximum Operating Pressure is 150 PSI @ 70° F.



Part No.	Max. PSI	Pipe Size	Opening Thru Ball
TK MV225CF	150	2"	2"

2" Full Port Stainless Steel Ball Valve



- Unique Compact Design.
- 100% PTFE Ball Seats.
- All TFE Seals. No Elastomers.

Part No.	Max. PSI	Pipe Size	Opening Thru Ball
TK VSFMT220SS	150	2"	2"

Viton® is a registered trademark of DuPont Performance Elastomers