

## (LP or Natural Gas)

**Stationary Natural Gas or LP Fired Pressure Washers** are engineered to provide maximum cleaning efficiency. Strong enough to tackle the most demanding cleaning jobs. Designed to provide water temperatures to 180° F. All units feature chemical solution system for injecting cleaning chemicals into the pumping line. All units feature *General* Plunger Pumps driven by electric motors.

**Standard Features Include:** Trigger spray gun with wand • 50' high pressure hose with quick couplers • Unloader valve • Safety pop-off valve • Flow switch for burner shutdown • Schedule 80 1/2" Coil • Adjustable Thermostat • Upstream high pressure chemical injection system • Low water shut-off • Draft diverters available as an option. Gas valves are 1". **Note: All units are fired and tested. (Please specify LP or Natural Gas). 5 Year prorated coils. Made in USA.**



Part No.	Flow	PSI	HP	Wt.
DU DS3-2400	3 GPM	2400	5 HP / 1 PH	725 lbs.
DU DS3-2400/3	3 GPM	2400	5 HP / 3 PH	725 lbs.
DU DS4-3000	4 GPM	3000	8 HP / 1 PH	800 lbs.
DU DS4-3000/3	4 GPM	3000	8 HP / 3 PH	800 lbs.
DU DS5-3000	5 GPM	3000	10 HP / 3 PH	860 lbs.
DU DS7-3000	7 GPM	3000	15 HP / 3 PH	1390 lbs.
DU DS10-2000	10 GPM	2000	15 HP / 3 PH	1640 lbs.
DU DS10-3000	10 GPM	3000	20 HP / 3 PH	1660 lbs.
DU Z01-00100	10" Draft Diverter as Add On for 3 GPM Units...			
DU Z01-00101	12" Std. Draft Diverter as Add On for 4-10 GPM Units			
DU Z01-00105	10" Motorized Draft Diverter, 3 GPM Units.....			
DU Z01-00104	12" Motorized Draft Diverter, 4-10 GPM Units....			
DU 12EIG	Electronic Ignition as Add On .....			
DU 12AUTO	Automatic Stop/Start Control - <b>Call for Pricing</b>			



**Provides Maximum Cleaning Efficiency!**



**EASY-KLEEN**  
PRESSURE SYSTEMS LTD.

**Easy to Use, Easy to Maintain, Easy to Service, Efficient to Run and Safe**

**Buffalo Series Standard Features:** General plunger pumps • Trigger spray gun with wand and nozzles • 50' of high pressure hose • Pressure relief valve • High pressure chemical injection • Water float tank • Quick Clean burners • Adjustable air flow vents • Auto On/Off with delay • 11 Gauge welded steel frame with powder coat finish • Adjustable thermostat • Schedule 80 or Schedule 160 coils sealed in ceramic blanket and stainless housing • TEFC 1 Phase or 3 Phase motors • Natural Gas or Propane, (Specify) • Belt drive pumps all units but EZ2435E1 and EZ3035E1 which are \* Direct Drive • Made in Canada, ships from U.S.



Part No.	Description
EZ 2435E1	* 3.5 GPM @ 2400 PSI. 5 Hp/1 Phase/220V. Rated to 290,000 BTU. 46" L x 32" W x 46" H. Wt. 400 lbs. ....
EZ 3035E1	* 3.5 GPM @ 3000 PSI. 7.5 Hp/1 Phase/220V. Rated to 290,000 BTU. 46" L x 32" W x 46" H. Wt. 415 lbs. ....
EZ 20041	4.0 GPM @ 2000 PSI. 5.0 Hp/1 Phase/220V. Rated to 390,000 BTU. 55" L x 30" W x 48" H. Wt. 800 .....
EZ 20043	4.0 GPM @ 2000 PSI. 5.0 Hp/3 Phase/220V/440V. Rated to 390,000 BTU. 55" L x 30" W x 48" H. Wt. 800.....
EZ 30041	4.0 GPM @ 3000 PSI. 7.5 Hp/1 Phase/220V. Rated to 390,000 BTU. 55" L x 30" W x 48" H. Wt. 800 lbs. ....
EZ 30043	4.0 GPM @ 3000 PSI. 7.5 Hp/3 Phase/208V/440V/575V. Rated to 390,000 BTU. 55" L x 30" W x 48" H. Wt. 800 lbs.....
EZ 40043	4.0 GPM @ 4000 PSI. 10 Hp/3 Phase/208V/440V/575V. Rated to 390,000 BTU. 55" L x 35" W x 48" H. Wt. 1100 lbs.....
EZ 60043	4.0 GPM @ 6000 PSI. 20 Hp/3 Phase/208V/440V/575V. Rated to 390,000 BTU. 68" L x 32" W x 51" H. Wt. 1300 lbs.....
EZ 30051	5.0 GPM @ 3000 PSI. 10 Hp/1 Phase/208V. Rated to 390,000 BTU. 68" L x 32" W x 51" H. Wt. 1300 lbs. ....
EZ 30053	5.0 GPM @ 3000 PSI. 10 Hp/3 Phase/208V/440V/575V. Rated to 390,000 BTU. 68" L x 32" W x 51" H. Wt. 1300 lbs.....
EZ 36083	8.0 GPM @ 3600 PSI. 20 Hp/3 Phase/208V/440V/575V. Rated to 720,000 BTU. 68" L x 32" W x 51" H. Wt. 1450 lbs.....
EZ PRO-DH8	8" Draft Diverter for 290,000 to 390,000 BTU's. ....
EZ PRO-DH10	10" Draft Diverter for 510,000 to 720,000 BTU's. ....

\* Direct Drive Pump/Motors.