


FILL-RITE 12 Volt Portable RD Series Pumps

*The Most Versatile DC Pump Available!
For Use With Gasoline & Other Flammable Liquids*

Features: Up to 8 GPM • Gasoline, diesel, biodiesel (up to B20), kerosenes & E15 • Aluminum construction • 3/4" Inlet/Outlet • Low profile • Thermally protected • Self-priming • 30 Minute duty cycle • Smooth in-line switch • U.L. listed.



RD812NH
Pump with Hoses & Nozzle

RD812NN
Pump Only


FILL-RITE

| Part No. | Description |
|------------|---|
| FR RD812NN | Pump Only , Includes 10' Quick Connect Power Cord With Alligator Clips, 12 Volt..... |
| FR RD812NH | Pump With Hose & Nozzle , Includes Manual Nozzle 8' Discharge Hose, 6' Suction Hose & 10' Quick Connect Power Cord With Alligator Clips, 12 Volt..... |
| FR RD812NP | Bung Mount Option Pump With Hose & Nozzle , Includes Manual Nozzle, 8' Discharge Hose, 23"-41" Telescoping Suction Tube, Nozzle Boot, Bung Tank Mount Adapter, 10' Quick Connect Power Cord with Alligator Clips, 12V..... |


Air Operated Diaphragm Pumps for Petroleum Products

FEATURES

- Non-Stalling
- Lube-Free
- Self-Priming (15' on Dry Prime)
- Use 1035 & 1040 for Oil, Waste Oil & ATF
- Use 1040UL for Gasoline & Diesel Fuel



1035



1040UL

Air operated 1:1 Double Diaphragm Pumps

| Specifications | 1035 | 1040 | 1040UL |
|-------------------|---------------|---------------|----------|
| Maximum Flow | 14 GPM | 37 GPM | 37 GPM |
| Inlet/Outlet | 1/2" NPT | 1" NPT | 1" NPT |
| Body Construction | Polypropylene | Aluminum/Poly | Aluminum |
| Diaphragm | Buna N | Buna N | Buna N |
| Balls | Acetal | Acetal | Teflon |
| Seats | Polypropylene | Aluminum | Aluminum |
| UL Listed | No | No | Yes |

| Part No. | Description |
|-----------|---|
| NS 1035 | Polypropylene, 1/2" NPT, 14 GPM..... |
| NS 1040 | Aluminum/Poly, 1" NPT, 37 GPM..... |
| NS 1040UL | Aluminum, 1" NPT, 37 GPM..... |
| NS 1559A2 | Air Filter, Regulator, Gauge, Ball Valve, Quick Disconnect Kit..... |
| NS 96 | Wall Mount Bracket..... |



FILL-RITE Rotary Vane Pumps - 12 Volt -

Economical pumps for light duty transferring of diesel, anti-freeze, transmission fluid & light oils. Self-priming. 3/4" FNPT inlet & outlet. Cast iron bodies, iron rotors, HNBR seals. Internal by-pass valve and battery cable with alligator clips included. Pump "Kits" also include 3/4", 8' suction hose with foot valve & 3/4" x 8' discharge hose with 3/4" poly nozzle. Pumps diesel at 10 GPM (at 9.5 PSI).

All models are rated for 30 minute duty cycle. 30 amp fuse included. Temperature rating: 0-100° F.



12 Volt

FR1612

Not for gasoline or other flammable liquids or water (not UL listed). Also Not for oils, motor oils or waste oils.

FILL-RITE



12 Volt

FR1614

| Part No. | Description | Ports | Voltage | Amp Draw | Kit |
|-----------|-----------------------|-------|---------|----------|-----|
| FR FR1612 | 12V Rotary Pump | 3/4" | 12 Volt | 20 Amps | No |
| FR FR1614 | 12V Rotary Pump "Kit" | 3/4" | 12 Volt | 20 Amps | Yes |

2" Bung Adapter Bushing



#600-105
Bushing
2" MPT x
2" MPT
1-1/4" FPT



1-1/4"x6"
Nipple or
1-1/4"
Suction
Pipe



1-1/4"x1"
Bell Reducer
(If 1" Suction
Pipe is Used)

600-105 Cast Iron Threaded Bung Adapter Bushing: 2" MPT x 2" MPT x 1-1/4" FPT for use with standard lever couplings, as shown. Allows quick transfer of pump from barrel to barrel without removing threaded fittings. **151-98 Suction Pipe** is adjustable from 20" to 34.75".

| Part No. | Description |
|----------------|--------------------------------------|
| FR 600-105 | Adapter Only..... |
| DU 1-1/4X48 | 1-1/4" Suction Pipe (48")..... |
| FR 151-98 | 1" Suction Pipe (Adj. 20" to 34.75") |
| US 678-1-1/4X1 | 1-1/4" x 1" Bell Reducer..... |

Suction Pipes for Fuel Pumps

— Steel Male Pipe Thread by Beveled Other End —

| Part No. | Description | Size |
|-------------|--------------|--------------|
| DU 1X48 | Beveled Pipe | 1" x 48" |
| DU 1X63 | Beveled Pipe | 1" x 63" |
| DU 1-1/4X48 | Beveled Pipe | 1-1/4" x 48" |
| DU 1-1/4X63 | Beveled Pipe | 1-1/4" x 63" |

Viton® is a registered trademark of DuPont Performance Elastomers