

Chlorine Carbon Filters



Chlorine Carbon Bottle with Auto Back Wash


Carbon Filters are designed for removing Chlorine from water supplies prior to Reverse Osmosis systems. Chlorine can damage RO membranes and shorten life. All units are standard with *Fleck* controls. Connection is 3/4" on L0005, L0006 and L0007. Connection is 1" on L0008 and L0009. Backwash feature is time clock activated.

Part No.	Cu. Ft.	Size	Service Flow Rate	Wt.
EP L0005FL	3/4	8" x 44"	1.75 GPM	65 lbs.
EP L0006FL	1	9" x 48"	2.2 GPM	75 lbs.
EP L0007FL	2	12" x 52"	3.95 GPM	120 lbs.
EP L0008	3	14" x 65"	5.35 GPM	180 lbs.
EP L0009	4	16" x 65"	7 GPM	230 lbs.

Sediment Cartridge Filters

Polypropylene String Wound or Spun Filter Cartridges. For replacement in all commercial single or multi-cartridge housings. Design provides clean, fresh water to RO Membranes or faucets. Filters impurities from 1 to 50 microns. Lengths shown will fit 10" or 20" filter housings. Rated service flows from 5-8 GPM. Diameter on these filters is 2-1/2" O.D. (*Fits WF housings on adjacent page.*)

Part No.	Style	Lgth	* Std Pkg
EP LP014	1 Micron Cartridge String	20"	20
EP LP013	5 Micron Cartridge String	10"	40
EP LP015	5 Micron Cartridge String	20"	20
EP LP017	20 Micron Cartridge String	10"	40
EP LP019	20 Micron Cartridge String	20"	20
EP LP024	1 Micron Cartridge Spun	10"	40
EP LP025	1 Micron Cartridge Spun	20"	20
EP LP026	5 Micron Cartridge Spun	10"	40
EP LP027	5 Micron Cartridge Spun	20"	20
EP LP023	50 Micron Cartridge Spun	20"	20



Spun Style String Wound

***Std Pkg Orders Receive an Additional 10% Discount**

Carbon Cartridge Filters



CFC01 Filter

Activated Coconut Carbon Filters are ideal for removing chlorine from water supplies prior to RO Systems. Protects and extends membrane life. 2-1/2" or 4-1/2" O.D. Fits filter housings shown on this page.

Part No.	Dimensions	Chlorine Capacity	* Std. Pkg.
EP CFC01	2-1/2" x 9.75"	4,000 Gal.	10
EP CFC05	2-1/2" x 20"	8,000 Gal.	12
EP CFC41	4" x 10"	10,000 Gal.	12
EP CFC45	4" x 20"	20,000 Gal.	6

***10% Discount if Ordered in Standard Packages**

Multi-Purpose Filter Housings



WF2124

Heavy Duty, Chemical-Resistant Polypropylene Filter Housings are designed for regular 2-1/2" or jumbo 4-1/2" sediment or carbon filters. **WF1124** and **WF2124** have 3/4" FPT ports. **WF4124** and **WF4140** have 1" ports. Leak-proof sealing rings. Pressure vents are standard. Temperatures to 125° F. Pressures to 75-100 PSI.



WF4124 "Big Blue"



WF1124



Filter Wrenches



This housing is tested and Certified by NSF International against NSF/ANSI Standard 42 for materials and structural integrity requirements.

Part No.	Overall Length	For Cartridge Sizes	* Std. Pkg.
EP WF1124	12"	2-1/2" x 10"	12
EP WF2124	22"	2-1/2" x 20"	
EP WF4124	12"	4-1/2" x 10"	
EP WF4140	22"	4-1/2" x 20"	
EP WR32	Filter Wrench, 2-1/2" Slim White Housings		
EP WR32A	Filter Wrench Regular Blue Housings		
EP WR42	Filter Wrench, 4-1/2" Housings		

***10% Discount if Ordered in Standard Packages**

CONTACT US FOR ALL YOUR PRODUCT NEEDS!



OMAHA, NEBRASKA
1-800-228-9666
FAX: 1-402-333-5546

DAVENPORT, IOWA
1-800-553-6975
FAX: 1-563-386-5448



www.dultmeier.com

Scan our QR Code



- Current Pricing
- Web Specials
- Closeout Items
- Current Flyers
- Order Status
- Parts Schematics



dultmeier.com