Micromatic Closed Drum Valves and Couplers for DEF

Micromatic Couplers are specifically designed for DEF. Constructed of 304SS with peroxide-cured EPDM Elastomers. Used on many DEF closed transfer tanks to prevent product contamination. Note: 4 Key is for DEF.



RSV Drum Valve

Reusable Stainless Valve

195205B Closed Stainless Steel RSV Series Drum

Valve. 2.5" x 5 buttress threads.





RSV Dispense Coupler

195205D Stainless Steel Dispense Coupler. For closed systems - 3/4" hose barb connection. Used with 195205B drum valve. Dispenses up to 24 GPM. Self-venting.

RSV Dispense Coupler

5662 Stainless Steel Dispense Coupler. For closed systems - 3/4" FPT 90° Outlet connection. Used with 195205B drum valve. Dispenses up to 24 GPM. Self-venting.





RSV Dispense Coupler

5072 Stainless Steel Dispense Coupler. For closed systems - 1" MPT straight vertical outlet connection. Used with 195205B drum valve. Dispenses up to 24 GPM. Self-venting.

195205F Stainless Steel Fill Coupler for filling closed systems using RSV drum valves. Allows approximately up to 49 GPM fill rate, coupler is self venting and has 1" MNPT inlet fitting. Used with 195205B drum valve. 1/4" FPT vapor recovery port.



MICRO MATIC

RSV SERIES

Part No.	
PJ 195205B	Micromatic 2" RSV "Drum" Valve for DEF
PJ 195205D	Micromatic RSV Coupler with 3/4" HB Inlet for DEF
PJ 5662	Micromatic RSV Coupler SS with 3/4" FPT 90- Connect.
PJ 5072	Micromatic RSV Coupler SS, 1" MPT Straight Vertical.
PJ 195205F	Micromatic Fill Coupler for DEF (Fill Only)

- Viton® Available -

Suction Tubes for RPV/RSV Series Drum Valves

Poly Flex Suction Tube Assembly for Drums & Totes - RPV or RSV Series. Straight Tubes



- Flex Tubes Available -

Part No.	<u>Description</u>
PJ 195205-32	Suction Tube For 55 Gallon Drums, 32" x 1"
PJ 195205-40	Suction Tube For 275 Gallon Totes, 38" x 1"
PJ 6790-1135	Suction Tube For 330 Gallon Totes, 45" x 1"

Micromatic

Closed Valves and Couplers for DEF

Note: 4 Key is for DEF.

RPV Dispense Coupler

195205P RPV Dispense Coupler, Works with stainless RSV or poly RPV valves, 3/4" Hose barb fitting. Dispenses up to 18 GPM. Self-venting.

RPV Dispense Coupler

195205P

6905 Dispense Coupler. Poly dispense coupler. EPDM for closed systems. 1"MPT Vertical straight outlet. Dispenses up to 18 GPM. Self-venting.



MICRO MATIC



195205E

Tamper Evident Cap

195205E Tamper Evident Cap. Protects RPV or RSV drum valves from dirt and debris when the RSV coupler is disconnected. HDPE construction.



RSV Series Drum Key

195205C RSV Series Drum Key. 304 Stainless Steel. For installation and removal of P/N 195205B drum valve. Uses 1/2" socket drive. Poly also available.



195205N

RPV Drum Valve

195205N RPV Drum Valve. Works with stainless RSV or poly RPV dispense or fill couplers.

NPT Adapter

560102 NPT Adapter. Allows the use of buttress threaded pumps to be used on drums with NPT threads. 2.5" Female buttress x 2" MPT.



560102



5792 Shown

Tote Caps

901081-A 6"IBCTote Cap with (1) 2.5" x 5 female buttress thread. Universal tank cap. 301-807 6" IBC Tote Cap with (1) 2.5" x 5 female buttress thread. Schutz Tanks Only. 5792 6" IBC Tote Cap with (2) 2.5" x 5 female buttress thread.

Part No. PJ 195205P PJ 6905 PJ 195205E PJ 195205N	Description RPV Dispense Coupler, 3/4" Hose Barb
PJ 195205N	RPV Drum Valve
PJ 195205C	RSV Series Stainless Drum Key
PJ 5541	RPV Series Poly Drum Key
PJ 560101	Adapter, 2.5" x 5 Male Buttress x 2" FPT
PJ 560102	Adapter, 2.5" x 5 Female Buttress x 2" MPT
PJ 901081-A	Tote Cap with (1) 2.5 x 5 Buttress Opening. Universal Tote Cap
PJ 301-807	Tote Cap with (1) 2.5" x 5 Buttress Opening for <i>Schutz</i> Tanks
PJ 5792	Tote Cap with (2) 2.5" x 5 Buttress Opening
PJ 2DV4-001 PJ 5356	4-Key Rinse Socket, 304SS, EPDM, Wall Mount

MICRO MATIC