## E1084 Nozzle Protectors & Holder • Solid Stream Nozzles

## **Nozzle Protectors**

Designed to protect vehicle surfaces from scratching and damage. Nozzles are completely surrounded by protector guards. Different style designs are shown below.

ST007 Nozzle Protector features a soft outer edge to protect surfaces and a Hard Plastic Base for added wear life. Inlet port is 1/4" FPT Stainless steel. Rated to 5,000 PSI and 300° F. Designed for 1/4" MPT nozzles. Over length is 2".



Inlet Part No. Nozzle Type Color **NP** ST107 Black/Red 1/4" FPT 1/4"



ST004 Nozzle Protectors feature a two piece design where the tough, plastic outer cover threads on to a plastic base. Zinc-plated, 1/4" FPT inlet fitting is housed in the base. Available for either 1/8" or 1/4" MPT nozzles. Rated to 5,000 PSI and 210° F. Overall length is 2-1/2".

Part No.	Inlet	Nozzle Type	Color
<b>NP</b> ST004-D42	1/4" FPT	1/8" MPT	Black/Gray
<b>NP</b> ST004-D44	1/4" FPT	1/4" MPT	Black/Gray

1830 Nozzle Protector features a 1/4" FPT plated inlet. Heavy wall, plastic construction is standard. Rated to 5100 PSI and 320° F. Designed for 1/4" MPT nozzles. Overall length is 2".





ST10 / ST15 Nozzle Protectors feature a brass, 1/4" FPT inlet and hard plastic upper cover. ST10 Designed for any 1/4" wand extensions including spring type flex extensions. Overall length is 1-1/4". Rated to 2000.

Part No.	Inlet	Nozzle Type	Color
<b>GS</b> ST10	1/4" FPT	1/8" MPT	Black
<b>GS</b> ST15	1/4" FPT	1/4" MPT	Black

140 Nozzle Protectors are made of a heavy plastic and are held in place by the nozzle and wand. The base acts like a washer to hold both together. Overall Length is 2-1/8". Available in blue, red or black. One-piece design. Also commonly used on triple foam wands.



Part No.	<u>Inlet</u>	Nozzle Type	<u>Colo</u>
<b>BC</b> 140	-	1/8" or 1/4" MPT	Blue
<b>BC</b> 140B	-	1/8" or 1/4" MPT	Black
<b>BC</b> 140R	-	1/8" or 1/4" MPT	Red




2200 Series Nozzle Protectors are made of heavy but flexible plastic and are held in place by the nozzle like the 140 series above. Overall length is 2-1/4". Available in blue or black. One-piece design.

Part No.	<u>Inlet</u>	Nozzle Type	Colo
<b>GS</b> 22002	-	1/8" or 1/4" MPT	Blue
<b>GS</b> 22005	-	1/8" or 1/4" MPT	Black



No. 26110-PUR

Durable and abrasion resistant polyurethane nozzle protector. Shields the spray surface from damaging



Also protects the nozzle & extends wear life. One size fits both 1/8" & 1/4" MEG nozzles up to #20 orifice. Maintains shape and durability from below freezing to 250° F.

Nozzle Protector

SS CP26110-PUR Nozzle Protector



## **Nozzle Holder**

Soft, Durable Polymer Nozzle Holder is designed to slip over your 1/4" spray lance. Keeps nozzles close for easy change out. Holds up to (4) quick connect nozzles (Not included). Rated to 140° F. for cold water applications.





Shown with Nozzles

Part No

NP 22515 Rubber Nozzle Holder .....



## Soap Shooter Injector/Nozzles

Downstream Chemical Injector/Shooter Nozzles from General Pump. Designed to throw chemical solutions to 30' high. Attaches to your wand extension quick coupler. Internal design does not require a Hi-Lo nozzle to function. Adjustable control knob to easily change from chemical to rinse at the wand and control injection ratios up to 12%. Stainless steel nozzle is rated to 5000 PSI. Complete assemblies include: nozzle body with Viton® O-ring, Adjustable chemical injector knob, 30' chemical supply line, inlet chemical filter, 1/4" male QC fitting and orifice from 3.5 to 7.0 to match your pump flow and pressure.





Part No.	Orifice	Max Pressure
<b>IP</b> 100169	3.5	5000 PSI
<b>IP</b> 100145	4.0	5000 PSI
<b>IP</b> 100146	4.5	5000 PSI
<b>IP</b> 100147	5.0	5000 PSI
<b>IP</b> 100181	6.0	5000 PSI
IP 101012	7.0	5000 PSI

Viton® is a registered trademark of DuPont Performance Elastomers