
# SuperKlean Wash Down Wands

- Rear Trigger -

Super Kleen Trigger Guns are designed for plant washdown, truck wash, tank cleanout and industrial cleaning. Rated to 7 gpm @ 50 psi and 12 gpm @ 150 psi. 200° F. maximum. Rear mounted levers reduce hand fatigue and offer smooth lever action. Variable spray pattern is adjustable from fan spray to solid stream. Inlet Port is 1/2" FPT. Rated to 23 GPM and up to 500 PSI. (150 PSI @ 200° F.)



Drip-free automatic shutoff is a standard feature. Available in Brass. Aluminum or Stainless Steel construction with Blue, White, Red or Gray covers. All covers are easily replaceable if required. Not for use with steam.







Part No.	<u>Body</u>	Cover	Wt.
<b>VD</b> 150ALB	Aluminum	Light Blue	1.7 lbs.
<b>VD</b> 150AR	Aluminum	Red	1.7 lbs.
<b>VD</b> 150AW	Aluminum	White	1.7 lbs.
<b>VD</b> 150BB	Brass	Dark Blue	3 lbs.
<b>VD</b> 150BR	Brass	Red	3 lbs.
<b>VD</b> 150BW	Brass	White	3 lbs.
<b>VD</b> 150SG	Stainless	Gray	2.8 lbs.

# SuperKlean\*

## **DuraSpray Inline Spray Wands**



DuraSpray Inline Spray Wands from Super Kleen are designed for overhead hanging hose applications. 304 Stainless bodies with optional cover colors. Rated up to 500 PSI, (150 PSI at 200° F.). 4.9 to 8 GPM at 75 PSI or 7 to 12 GPM at 150 PSI. Safety trigger lock feature prevents accidental spraying. Inlet is 1/2" FPT.








**Body** Cover Wt. 304SS Blue 1.40 lbs. 304SS 1.40 lbs Red 304SS White 1.40 lbs.

# SuperKlean Thermosmart **Spray Wands**



Super Kleen Thermosmart Spray Wands have the same features as the wands at left, but have the added feature of a built-in temperature indicating window with safety cover. USDA/FDA compliant for correct output temperatures.

The USDA is actively promoting that the food industry maintain wash water temperatures above 165° F. This wand design allows operators to know immediately what the output temperature is. Brass, aluminum or Stainless construction with White cover.



### SuperKlean"

### **Wash Down Wands**

- Front Trigger -

Super Kleen DuraFlow Front Trigger Spray Gun is designed for plant washdown, truck wash, tank cleaning and industrial spraying. Unique design allows for variable spray pattern from a fan to solid stream. Automatic, drip-free shut-off is also a standard feature. Rated for 200° F. and 150 PSI, water only - Not for use with steam.



Part No. Body **VD** DH150SDB Stainless VD DH150SR Stainless VD DH150SW Stainless



Front trigger can be locked to maintain any nozzle pattern. Stainless steel body with durable cover. Rated to 6.5 GPM at 50 PSI and 11.90 GPM at 150 PSI. Weight is 1.53 lbs.



Cover **Dark Blue** Red White