



## Cone Bottom Storage Tanks

175 Gallons thru 500 Gallons

- Heavy duty polyethylene with ultra-violet inhibitors added for protection against sunlight. Poly stands.
- Offset fillwell & cover standard.
- Sidewall flat for recirculation.
- 30° cone for tanks.
- Molded-in gallonage marks.
- Standard color is White.

**WARRANTY:** 3-Year from factory ship date on cone bottom storage tanks - non-mobile applications.

**NOTE:** These tanks designed for 12 lb/gal. liquids.

### - Cone Bottom Tanks with Poly Stands -

Part No.	Capacity	Diameter	Height	Fillwell	Poly Fitting	Call Toll Free For Prices
RV 60113	175 Gallon	42"	49"	10"	3/4"	
RV 62441	310 Gallon	42"	71"	16"	2"	
RV 40289	500 Gallon	48"	85"	16"	2"	

## Freshwater Tank



A **9-Gallon Freshwater Tank** with a hinged lid over a recess in the tank which can be used to store items required by **EPA's Worker Protection Standard (40 CFR170)**.

The tank is designed so it can be mounted on spraying applicators or other equipment involved in the handling and application of pesticides. Tank is a white polyethylene to show level indicators and ensure compliance with FDA regulations. For mounting, 4-5/16" nuts are molded into the tank side and bottom. Includes 3/4" FPT port for D1050 spigot valve.

**Size:** 10"W, 14"H, 20"L

**Note:** Tank should be flushed and refilled on a regular basis.

Part No.	Description	Call Toll Free For Prices
RV 47036	Safety Tank with Storage Compartment	
RV 5461R	Screw On Lid for #26676.....	

## Polyethylene Round Pallet Paks

— Forkliftable —



VT110



VT210

**Bottom Outlet Fitting can be added. Rated to 1.7 S.G. (14 lbs/Gallon)**

Part No.	Capacity	Lid	Top Outlet	Diameter	Base	Call Toll Free For Prices
RT VT110	110 Gallon	5"	2"	33"	Square	
RT VT0210-PP	210 Gallon	5"	2"	41"	Round	

## 40 & 60 Gallon Blow-Molded Poly Tanks

Constructed of blow-molded low density polyethylene with UV inhibitors for economy and lightweight. Both tanks include molded-in legs with black anchor feet, end sump with 3/4" drain cap, 5" lid with lanyard, band locator grooves and 4X10-24 brass inserts for pump mounting, and hose warp "horns". Translucent with gallonage indicators. Rated for 14 lb./gal. liquids. Standard white color (Yellow available).



Part No.	Capacity	Lid	Length	Width	Height	Wt.	CALL for CURRENT PRICING
RT SB40	40 Gallon	5"	36"	24"	19"	17.5 lbs.	
RT SB60	60 Gallon	5"	36"	24"	26"	21.0 lbs.	
RT 12499	Replacement 5" Lid with Lanyard (Drilled Hole Vent) .....						
RT 13696	Replacement 5" Lid with Lanyard (Spring Loaded Vent in Lid) .....						

\* 30 Gallon Includes Spring Loaded Vent in Lid (RT 13696)



## Dual Containment Tanks

The **Dual Containment Tank (DCT)** from Snyder Industries is one of their latest product innovations. These double wall containment tanks range from 35 gallon capacity up to 1500 gallon capacity. This product provides end users with a secondary containment solution in one integral space saving unit. While the **Captor Containment System** is Snyder Industries' work horse, the DCT product line is an ideal solution for commercial "Day" tank system requirements.

- **DCT Systems** use bolted double wall flanged fittings (recommended) or a bulkhead-style fitting
- All primary tanks come with noted specific gravity while all secondary tanks are made from HDLPE, 1.9 S.G. Rated, Natural resin
- **DCT** sidewall fitting locations are at 0°, 90°, 180°, 270° only – see **CPT** systems for more versatility in fitting configurations



**Call for Pricing & Availability On Your Specific Configuration Needs!**

Viton® is a registered trademark of DuPont Performance Elastomers