Lube Equipment Packages



Lube Equipment Packages

We offer a wide selection to accommodate all of your oil/grease application needs. Should you not find a unit that meets your requirements, please, call us for consultation and we will be happy to locate a unit to meet your needs. Air Ratio describes the amount of work an air operated pump is able to do. To figure the output PSI, simply multiply the first number of the ratio by the air pressure being fed into the pump. For example, a 3:1 ratio pump operated at a supply pressure of 100 PSI will produce 300 PSI of outlet pressure.

* Note: All Oil/Grease Equipment Packages come with hose installed on reel.

Oil Equipment Packages

No. 6105: 3:1 Ratio pneumatic Stub pump with a 5 GPM fluid delivery rate. Stub pumps do not include pickup tube for containers – must be ordered separately. Hose reel comes with 1/2IN x 49FT hose installed. Digital meter dispenses in pints, quarts, liters, or gallons – no totalizer. Does NOT included NS148 cart.

No.6120: Same as NS6105 but pump delivers 3 GPM flow rates. Package includes mechanical preset meter that dispenses in quarts and totalizes in gallons. Does NOT included NS148 cart or NS15212 pickup tube.

No. 6401: 3:1 Ratio pneumatic pump to fit 55 gallon drum *(pickup tube included)*. Pump delivers 3 GPM flow rates. Hose is 1/2IN x 32FT. Digital meter that dispenses in pints, quarts, liters, or gallons. **NS148** cart included.



Oil Equipment Packages

Part No.	Description
NS 6105	3:1 Stub, 5 GPM Delivery Rate, 1/2" x 49' Hose, Digital Meter
NS 6120	3:1 Stub, 3 GPM Delivery Rate, 1/2" x 49' Hose, Mechanical Preset Meter
NS 6401	3:1 55 Gallon Drum Fitted, 3 GPM Delivery Rate, 1/2" x 32' Hose, Digital Meter
NS 148	4 Wheeled Cart for Oil Transfer Packages
NS 15212	Pickup Tube: 3/4" x 28" for 55 Gallon Drum
NS 15219	Pickup Tube: 1" x 24" for 16 Gallon Drum
NS 15223	Pickup Tube: 1" x 28" for 55 Gallon Drum
NS 2225	Replacement Hose: Medium Pressure Hose Assembly, 1/2" x 25' Fiber Braid,
	Maximum Working Pressure is 1125 PSI (1/2" Inlet/Outlet MPT)
NS 2250	Replacement Hose: Medium Pressure Hose Assembly, 1/2" x 50' Fiber Braid,
	Maximum Working Pressure is 1125 PSI (1/2" Inlet/Outlet MPT)



Tote Mounting Plate & Tote Dispensing System

6614: 3:1 Ratio pneumatic Stub Pump with a 5 GPM fluid delivery rate. 1/2" x 32' Hose on reel. Digital meter dispenses in pints, quarts, liters or gallons. **NS15216** Pickup tube (3/4" x 44") is included with this package.

6602: Universal Tote Mounting Plate Kit - plate and hardware only.



Part No. Pump NS 6614 Pump: 5 GPM Maximum Flow Rate, Hose Reel, Meter & Mounting Kit NS 6602 Universal Tote Mounting Plate Kit

Grease Equipment Packages

No. 6167: 65:1 Ratio pump delivers maximum 66 ounces per minute at 90 PSI. Air consumption is 8.74 CFM at 100 PSI. Air inlet is 1/4" MPT. This unit is designed to dispense from a 120 lb. drum. Hose is 1/4"IN x 52FT. No dolly included. Package includes air filter with night time drain, regulator, gauge, ball valve, quick disconnects and all connecting components. Pump and hose reel only. Hose reel is for wall or floor mount. Dolly/Drum <u>NOT</u> included.



NATIONAL - SPENCER, INC.

Grease Equipment Packages

Part No.	Pump
NS 6167	65:1 Pump, 66 oz., Maximum Flow at 90 PSI
NS 1850	High Pressure Hose Assembly, 1/4" x 50' MPT Both Ends
NS 120S	Drum Dolly for 120 lb. (16 Gallon) Drum

