

## HIGH PRESSURE REELS

### High Pressure Hose Reels



**High Pressure Hose Reels** are ideal for floor mount or frame mounting on pressure washers. Black, powder-coated finish. Hose guide is a standard feature for ease of use. Rated to 5,000 PSI and 212° F. Swivel is 3/8" FPT. Locking pin is included.

Part No.	Hose Capacity	Wt.
FN 80225	3/8" x 100'	22 lbs.
FN 80226	3/8" x 200'	31 lbs.

### Hand Carry Hose Reels

These reels are ideal for use with jetting machines, pressure washers or carpet solution hose. Rated to 5,000 PSI and 250° F.



**DHRHC50100** is a powder-coated steel reel with stainless base and handle. Capacity is 150' of 1/4" or 100' of 3/8" hose.

**DHRHC50150SS** is an all-stainless reel and frame. Capacity is 200' of 1/4" or 150' of 3/8" hose.

**2100012** optional jetter valve package includes valve, bracket and 3 jetter nozzles.

Part No.	Description	Wt.
IP DHRHC50100	Power Coat	24 lbs.
IP DHRHC50150SS	Stainless	24 lbs.
IP 2100012	Jetter Valve add on kit	3 lbs.

### Portable Jetter Reel & Hose Unit

**Simply Attach to Your Jetter or Pressure Washer**

**Compact and Easy-To-Use Jetter Reel** includes 100' of 1/4" jetter hose, hand carry reel, inlet shut-off valve, laser jetting nozzle and inlet quick connect fitting. Rated to 4000 PSI. Simply attach to your jetter or pressure washer.



Part No.	Hose	Max. PSI	Wt.
DU PT100R	1/4" x 100'	4,000	35 lbs.

### Hand Trigger Jetter Hose Assembly

**Simply Attach to Your Pressure Washer or Jetter Unit**

**Easy-To-Use, Compact Jetter Hose Assembly** with trigger handle, 50' of 1/4" jetter hose, trigger control wand, laser jetting nozzle, inlet valve and inlet quick connect fitting. Rated to 4000 PSI. Ideal for jetting needs in tight or closed spaces. Simply attach to your pressure washer or jetter unit.



Part No.	Hose Length	Max. PSI
DU PT50H	50'	4,000

**We Carry a Complete Line of Hose Reels!**

## AIR REELS



### Power Cord Reels

**Spring Rewind Power Cord Reels** have a compact design for critical space requirements. Corrosion-resistant, baked-on finish. Can be mounted to wall, ceiling or bench. Supplied with 4' inlet cord, power cord, hose guide and cord stop.



L4050-1633

Part No.	Cord Length	Rating	Wt.
RF L4050-1633	50'	13 Amp / 115 volt	26 lbs.
RF L4545-1233	45'	15 Amp / 115 Volt	28 lbs.
RF L4545-1233A	45'	20 Amp / 125 Volt	29 lbs.



### Enclosed Air Reel

**Standard Features:**

- Allows for 50' of Capacity
- Hose Inlet/Outlet is 3/8"
- Working Pressure of 300 PSI
- Advanced Auto Stop & Automatic Guide System
- Hose Can Be Stopped at Any Point & a Controlled Return Allows the Hose to Safely Guide Back Into the Enclosed Housing
- Compatible with Air or Water
- Bracket Allows for 180° of Swivel
- 3/8" x 50' of Hose Included



Part No.	Description
NS 1459NS	3/8" x 50' Enclosed Hose Reel, Spring Return .....

### Light Duty Air Hose Reels

**Light-Duty Steel Reels** are an ideal choice for air/water supply lines in shops or garages. Hand crank design with balanced brass swivel.



CU6050LN



CU6100LN

Inlet and outlet are 3/8" FPT. Rated to 250 PSI. Can be mounted on floor or wall. Both reels are 11-1/2" high x 11" deep. *Hose is not included.*

Part No.	Hose Capacity	Width	Wt.
RF CU6050LN	50' of 3/8" I.D.	17-1/4"	10 lbs.
RF CU6100LN	100' of 3/8" I.D.	21"	13 lbs.



### Spring Rewind Air Reel

**Spring Rewind Air Reel** features a composite PVC outer case which is corrosion-resistant. Solid brass swivel and steel main shaft are standard features. Positive latching system design. Can be mounted in any position on floor, wall or ceiling. Lightweight yet durable. 3/8" x 50' air hose is included and is rated to 230 PSI.



SGA3650OLP

Part No.	Wt.
RF SGA3650OLP	Spring Rewind Reel with Hose 23 lbs.