E1370

Ä

Under Carriage Cleaning Ramps

Under Carriage Cleaning Ramps

- mosmatic. Ramp Systems Only No Pumps—
- Construction
- Fleets
- Agriculture

80508

Mining

An Ideal System for Cleaning Over-The-Road & Fleet Vehicles

Undercarriage, High Pressure Ramps protect Fleet and Over-the-Road vehicles by thoroughly cleaning and rinsing the underside of your trucks, vans, cars and even 18 wheelers. Effectively removes chemicals, corrosives, dirt, sand, salt and mud build up.

Greatly reduces time to clean hard-to-reach areas. Increases vehicle life and makes for safer service and maintenance. High-quality Stainless Steel construction with Swiss engineering.


These unique ramps are designed to be operated in conjunction with your high pressure cold or hot, (250° F.) water cleaning machines. (Dultmeier Pump units are available if required to meet your needs).

Stainless Steel Ramps can be permanently mounted or can be easily moved to other locations if needed.

Stabilizer spinner nozzles create a high pressure, rotating water stream that effectively cleans up to 4-5 feet from the ramp surface so even high wheelbase vehicles can be effectively cleaned. Nozzle orifices are matched to your pump flow and pressure for optimal performance.



Optional Side Wheel Blasters and Support stands allow for added cleaning of wheel wells, tires and rocker panels or vehicle side panels. Can be mounted to either ramp, (order separately).



1 Pan 2 Rotors

6 to 20 gpm @ 1000 PSI. Dimensions are 104" wide, 67" long, 5" high. 80506 Same as above but with side riggers, pans and wheel blasters. Add 96" to width.

80646 Two Pan 4 Rotor Ramp is designed for extra heavy mud or sludge removal. Includes 4 complete nozzle assemblies. Rated up to 40 GPM @ 1000 PSI. Dimensions are 104" wide x 96" long x 5" high. Note: Add 96" to width if side riggers and side pans are ordered.

80550 Stainless Side Riggers attach to the side of either ramp and are designed to support wheel stands, (2 required per ramp). Optional, not required.

903986 Stainless Support Stands are 39" high and allow for adjustment of wheel pans for most effective cleaning. These attach to side riggers and support 84589 & 84599 wheel pans. (2 required per ramp). Optional, not required.

84589 Stainless Wheel/Tire Pan features stabilizer nozzles for exceptional cleaning and rinsing of wheel wells, tires, rims and rocker panels. Can be easily adjusted for different height and angle requirements. (2 required per ramp). Optional, not required. Fits 903986 pole.

84599 Stainless Side Rinse Pan features stabilizer nozzles for exceptional cleaning and rinsing of vehicle side panels and/or windows. (2 required per ramp). Requires support stand and/or support stand extension.

84907 Stand Extension fits 903986 stand.

Note: These Ramps are Not Compatible with VFD Pump/Water Units.



Description	Wt.
Stainless 1-Pan 2 Rotor Ramp	412 lbs.
Stainless 1-Pan Complete with Side Pans & Wheel Blasters	500 lbs.
Stainless 2-Pan 4 Rotor Ramp	825 lbs.
Stainless Side Rigger	10 lbs.
Stainless Support Stand, 39"	16 lbs.
Stainless Wheel Well Blaster	8 lbs.
Stainless Side Vehicle Blaster	10 lbs.
Stainless Support Stand Extension	13 lbs.
	Stainless 1-Pan 2 Rotor Ramp Stainless 1-Pan Complete with Side Pans & Wheel Blasters Stainless 2-Pan 4 Rotor Ramp Stainless Side Rigger Stainless Support Stand, 39" Stainless Wheel Well Blaster Stainless Side Vehicle Blaster

84589



80506





DULTMEIER SALES • OMAHA, NE (800) 228-9666 • www.dultmeier.com • DAVENPORT, IA (800) 553-6975

IND CW