# E1389 Mat Containment Systems • Dike Berms





Foam Berm Insert

## **Wash Mat Containment Systems**

Wash Mat Containment Systems from Latimat are an ideal choice for capturing water and chemical run-off from Fleet vehicles and Over-the-Road trucks. Portable design can be easily moved and set up as needed. Required in most states for high pressure cleaning of vehicles to keep contaminants and run-off from entering storm sewers.

Mats have 3-1/2" foam sidewalls and are designed so that vehicles with regular vehicle tires can easily drive over the sidewall berms to enter or leave the mat. (*Track mats options are also available for washing skid loaders, bull dozers, etc.*)

A sump pump or vacuum with discharge hose, (sold separately) transfers wastewater to your truck or holding tank.

Heavy-duty 22 oz. PVC mats are available in a wide variety of sizes to meet almost any vehicle washing requirement. **LWP0808FT** mat is an ideal size to catch run-off occurring from trailer washout.

**Note:** Mats can be used on smooth concrete or asphalt surfaces without protective underlays but warranty is void if punctures occur and underlay mats have not been used. For rough surfaces underlay mats are always required. All underlay mats are 2' larger on each side than Pad mats for added protection.



## **Wash Pad/Underlay Combination are Free Freight**

| <b>Wash Pad Mat</b> | s Size        |               |                 |
|---------------------|---------------|---------------|-----------------|
| Part No.            | $W \times L$  | Rating        | Wt.             |
| <b>LT</b> LWP0808F4 | 8' x 8'       | 22 oz.        | 21 lbs.         |
| <b>LT</b> LWP1020F4 | 10' x 20'     | 22 oz.        | 67 lbs.         |
| <b>LT</b> LWP1025F4 | 10' x 25'     | 22 oz.        | 84 lbs.         |
| <b>LT</b> LWP1216F4 | 12' x 16'     | 22 oz.        | 65 lbs.         |
| <b>LT</b> LWP1235F4 | 12' x 35'     | 22 oz.        | 140 lbs.        |
| <b>LT</b> LWP2035F4 | 20' x 35'     | 22 oz.        | 233 lbs.        |
| <b>LT</b> LWP1530F4 | 15' x 30'     | 22 oz.        | 150 lbs.        |
| <b>LT</b> LWP1540F4 | 15' x 40'     | 22 oz.        | 200 lbs.        |
| <b>LT</b> LWP1575F4 | *15' x 75'    | 22 oz.        | 370 lbs.        |
| GJ 5MSP             | Sump Pump     | , 115 Volt, 1 | 8' Cord, 9 lbs. |
| TF K1134-1          | 1" Transfer H | lose, per fo  | ot              |

<sup>\*</sup> For 18 Wheel Tractor/Trailer Units.

| Underlay               |                                |        |          |
|------------------------|--------------------------------|--------|----------|
| <b>Protective Mats</b> | Size                           |        |          |
| Part No.               | $\mathbf{W} \times \mathbf{L}$ | Rating | Wt.      |
| <b>LT</b> ULL1010      | 10' x 10'                      | 70 mil | 22 lbs.  |
| <b>LT</b> ULL1222      | 12' x 22'                      | 70 mil | 57 lbs.  |
| <b>LT</b> ULL1227      | 12' x 27'                      | 70 mil | 71 lbs.  |
| <b>LT</b> ULL1418      | 14' x 18'                      | 70 mil | 53 lbs.  |
| <b>LT</b> ULL1437      | 14' x 37'                      | 70 mil | 113 lbs. |
| <b>LT</b> ULL2237      | 22' x 37'                      | 70 mil | 177 lbs. |
| <b>LT</b> ULL1732      | 17' x 32'                      | 70 mil | 116 lbs. |
| <b>LT</b> ULL1742      | 17' x 42'                      | 70 mil | 152 lbs. |
| <b>LT</b> ULL1777      | 17' x 77'                      | 70 mil | 275 lbs. |
|                        |                                |        |          |


#### **Waste Water Dike Berms**

Portable Waste Water Dike Berms from Latimat are designed to hold back and capture waste water for transfer to holding tanks by use of sump pumps or vacuums, (sold separately). Keeps water run-off from entering storm sewers during vehicle or lot washing. Required by many state and municipality regulations.

Berms are 20 oz. PVC and available in 10', 20' or 50' lengths x 6" diameter. Simply fill berm 1/2 full with water in the summer or water/glycol in the winter to create the berm. Heat welded design with a 1" bar weld flap keeps dike from rolling when water is pooled against it.

Berms can be used straight or bent to shape as needed. Valves on each end to easily fill and empty. Can be rolled up when empty for transport or storage. Surfaces need to be swept clean and smooth for proper seal and water capture.

TF K1134-1





1" Transfer Hose, per foot .....