CRX Professional Gas Engines

- World Class Design & Innovation -

High Quality, Professional Grade CRX Gas Engines from *Simpson* are ideal for a wide variety of power requirements. World class design and innovation. Interchangeable with many of the most common engines in the market today. 4-1/2 to 32 HP. Available with recoil start or 12-volt electric start with alternators. All models feature low oil shutdown, air cooled, single or twin cylinders, overhead valve and splash lubrication. Emissions ratings approved for 49 states. *3-Year warranty*.



Single Cylinder with Attached Fuel Tanks

CRX165: 4.4HP / 163cc • Single Cylinder • 3/4" solid shaft • Dual element air cleaner • Low oil shutdown • .7 gallon fuel tank capacity • Recoil start.

CRX208/210: 5.7HP/208cc • Single Cylinder • 3/4" solid shaft • Dual element air cleaner • Low oil shutdown • .7 gallon fuel tank capacity • Recoil start.

CRX225: 6.2HP / 224cc • Single Cylinder • 3/4" solid shaft • Dual element air cleaner • Low oil shutdown • .7 gallon fuel tank capacity • Recoil start or 12-volt start.

CRX275: 7.7HP / 272cc • Single Cylinder • 1" solid shaft • Dual element air cleaner • Low oil shutdown • .8 gallon fuel tank capacity • Recoil start.

CRX420CC: 12.1HP/420cc • Single Cylinder • 1" solid shaft • Dual element air cleaner • Low oil shutdown • 1.6 gallon fuel tank capacity • Recoil start or 12-volt start with 20 amp alternator.





(Bulk Engines, No Box, LTL Truck Ship Only)

Part No.	<u>Size</u>	Starter	Shaft	<u>Box</u>	Wt.	
FN CRX208CC	5.7 HP/208cc	Recoil	3/4"	No	33 lbs.	
FN CRX225E	6.2 HP/224cc	12 Volt	3/4"	No	33 lbs.	
FN CRX420CC	12.1 HP/420cc	Recoil	1"	No	67 lbs.	
FN CRX420CC/F	12.1 HP/420cc	12 Volt	1"	No	67 lbs.	_

(Boxed Engines for UPS Ship)

Part No.	Size	Starter	Shaft	<u>Box</u>	Wt.	
FN CRX165	4.4 HP/163cc	Recoil	3/4"	Yes	36 lbs.	
FN CRX210X	5.7 HP/208cc	Recoil	3/4"	Yes	36 lbs.	
FN CRX225X	6.2 HP/224cc	Recoil	3/4"	Yes	36 lbs.	
FN CRX225EX	6.2 HP/224cc	12 Volt	3/4"	Yes	36 lbs.	
FN CRX420CCX	12.1 HP/420cc	Recoil	1"	Yes	70 lbs.	
FN CRX420CC/EX	12.1 HP/420cc	12 Volt	1"	Yes	70 lbs.	

V-Twin Engines for *External Fuel Tanks

CRX680CC: 19.5HP / 678cc • V-Twin, Overhead Valve • 1" solid shaft • Dual element air cleaner • Low oil shutdown • Requires external fuel tank • 12-volt starter with 20 amp alternator • Muffler included.

CRX750CC: 21.5HP / 750cc
V-Twin, Overhead Valve
1-1/8" solid shaft
Dual element air cleaner
Low oil shutdown
Requires external fuel tank

• 12-volt starter with 20 amp alternator • Muffler included.

CRX1000: 32.1HP / 999cc • V-Twin, Overhead Valve • 1-1/8" solid shaft • Cyclonic air cleaner • Low oil shutdown • Requires external fuel tank • 12-volt starter with 20 amp alternator • Muffler included.

* Note: External Fuel Tanks are Not Included with V-Twin Engines and Must Be Sourced Separately







(Boxed, Truck Ship Only)

Part No.	Size	Starter	Shaft	<u>Box</u>	Wt.
FN CRX680CC	19.5 HP/678cc	12 Volt	1"	Yes	109 lbs.
FN CRX750CC	21.5 HP/750cc	12 Volt	1-1/8"	Yes	109 lbs.
FN CRX1000	32.1 HP/999cc	12 Volt	1-1/8"	Yes	135 lbs.