12-Volt Wash Down Units

Pumptec 12-Volt Wash Down Units

featuring the X Series pump with ceramic plungers. Fill and wash down in one unit. Two models to choose from. Both include pump, motor, inlet plumbing kit, 25' discharge hose and adjustable spray wand. (Available in 120 or 240 volt if required).



12-Volt Pressure Washer Kits

The Industry Standard for 12 Volt DC Powered Pressure Washers

Compact 12-Volt Pressure Washer Kits are simple, fast, quiet and reliable. Sealed motors with push/pull switch and circuit breaker. All kits include unloader valve, spray wand, 25' spray hose (PWK15 only), suction filter and inlet hose, and motor mounts. This system is a simpler, more compact and lower in cost. Can be easily mounted to your equipment frame.



12-Volt Pressure Washer

12-Volt Pressure Washer featuring Cat plunger pump with built-in unloader and chemical injector. Designed to be easily mounted on your equipment frame and powered from your existing battery. Output is 1.50 GPM at 1000 PSI. Motor is 12-volt, 1 Hp, 80 full load amps. 25' Spray hose and trigger wand with 18" extension are standard. 3/8" Brass quick couplers to easily remove hose from pump are also included. 15" x 10" Baseplate available if needed.



55 lbs.

Output

DU PMV700 1.5 GPM @ 700 PSI

12-Volt Soft Wash Pump Unit



12-Volt Soft Wash Pump Unit from

Pumptec is engineered for compatibility with common Soft Wash applications. Up to 35' vertical and 50' horizontal spray throw. Includes PVC pump with Teflon/Carbon seals, ceramic plungers and C276 valves. Units include 12 volt motor, pump and pressure relief valve. Motor requires 71 amp for full output.

Part No. Flow **Pressure** PX 81810 45 lbs. 150 PSI

HAND CARRY LOW FLOW PRESSURE WASH UNITS

Low Flow, Medium Pressure, Wash Units can be used for light duty pressure washing as well as for Hard surface cleaning or use with low pressure extractors for carpet cleaning. Compact, hand carry design. (Note: these are pump/motor units only without hose or wands which can be ordered separately if needed).

Model 81887 is rated to 1.41 GPM @ 500 PSI with #4 nozzle. Standard features include • Pump with aluminum body, Buna seals, Stainless valves and plungers . Adjustable pressure control • Pressure gauge • 1/2HP motor, 120 volt, 7amp with on/off switch • 35' power cord • Mounting rails with vibration dampeners.



Part No. **Flow Pressure** Motor Wt. 1-1/2 HP, 1 Phase 51 lbs PX 81887 1 41 500 PSI



Model 80346 is rated to 2.2 GPM @ 1200 PSI with #4 nozzle. Ideal for general cleaning or hard surface cleaning. Can be used to pressurize any standard spinner tool. Use with wet/dry vacuums or portable extractors for optimum tile and grout cleaning.

Standard Features Include: Adjustable pressure control from 50 to 1200 PSI • Pressure gauge • 35' power cord • Motor is 1-1/2 HP, 1 Phase, 120/230 volt, 15/8 amp with on/off switch . Mounting rails with vibration dampeners.

Part No. Flow Pressure Motor PX 80346 1-1/2 HP, 1 Phase 60 lbs. 1200 PS

