

NYLON HOSE FITTINGS

Nylon fittings are usually good to 150 PSI and 175° F. They have good resistance to most agricultural chemicals, non-acid based fertilizers, petroleum fuels, ethanol, and most sodium chemicals. They should not be used with acid based fertilizers, chlorine, fluorides, xylene, compressed gases or hydrochloric, sulfuric, nitric or phosphoric acid.

NYLON HOSE MENDERS



Part No.	For I.D. Hose	Std. Pkg.	Std. Pkg. Discount
TW SHM1400	1/4" x 1/4"	50	25%
TW SHM3814	3/8" x 1/4"	25	25%
TW SHM3800	3/8" x 3/8"	50	25%
TW SHM1238	1/2" x 3/8"	50	25%
TW SHM1200	1/2" x 1/2"	50	25%
TW SHM5800	5/8" x 5/8"	25	25%
TW SHM3400	3/4" x 3/4"	25	25%
TW SHM1000	1" x 1"	25	25%
TW SHM114	1-1/4" x 1-1/4"	10	25%
TW SHM112	1-1/2" x 1-1/2"	10	25%
TW SHM200	2" x 2"	1	-
EV TM46	4" x 4"	1	-

NYLON ELBOW HOSE BARBS



Part No.	Hose Barb	STD. PKG.	Std. Pkg. Discount
TW EL3838HB	3/8" x 3/8"	50	25%
TW EL1212HB	1/2" x 1/2"	50	25%
TW EL58HB	5/8" x 5/8"	25	25%
TW EL3434HB	3/4" x 3/4"	25	25%
TW EL100HB	1" x 1"	25	25%
TW EL200HB	2" x 2"	5	25%
TW EL112HB	1-1/2" x 1-1/2"	10	25%
TW EL114HB	1-1/4" x 1-1/4"	10	25%

NYLON HOSE BARB TEES



Part No.	For I.D. Hose	Std. Pkg.	Std. Pkg. Discount
TW T14	1/4"	50	25%
TW T38	3/8"	50	25%
TW T12	1/2"	10	25%
TW T58	5/8"	10	25%
TW T34	3/4"	10	25%
TW T3412	3/4" X 1/2"	10	25%
TW T100	1"	10	25%
TW T114	1-1/4"	10	25%
TW T112	1-1/2"	10	25%
TW T200	2"	10	25%




POLY WYES

Part No.	Description
AF Y14N	1/4" Polypropylene WYE.....
AF Y38N	3/8" Polypropylene WYE
AF Y12N	1/2" Polypropylene WYE

Weld King Nipples (Hose Barbs)

Beveled End for Welded Connections
Unplated Steel or Stainless Steel



Beveled End for Welded Connections
- Unplated Steel -

Part No.	Size	Net Ea.
EV STB20	1-1/2"	\$ 10.30
EV STB25	2"	12.50
EV STB30	2-1/2"	6.40
EV STB35	3"	24.60
EV STB40	4"	13.00
EV STB50	5"	23.60
EV STB60	6"	28.25
EV STB80	8"	138.00

Beveled End for Welded Connections
- Stainless Steel (316SS) -

Part No.	Size
EV RSTB20	1-1/2"
EV RSTB25	2"
EV RSTB35	3"
EV RSTB40	4"
EV RSTB60	6"

King Nipples in Jump Sizes

- Plated Steel -

Part No.	Hose Shank	Male NPT
EV STC1015	1"	1-1/4"
EV STC1510	1-1/4"	1"
EV STC1520	1-1/4"	1-1/2"
EV STC2015	1-1/2"	1-1/4"
EV STC2025	1-1/2"	2"
EV STC2520	2"	1-1/2"
EV STC2535	2"	3"
EV STC3525	3"	2"
EV STC3540	3"	4"
EV STC4035	4"	3"



HOSE MENDERS

BRASS HOSE MENDERS *

Rated to 150 PSI W.P.
Hose Barb x Hose Barb

Part No.	Description
EV BM2	1/4" Brass Hose Mender.....
EV BM3	3/8" Brass Hose Mender.....
EV BM4	1/2" Brass Hose Mender.....
EV BM5	5/8" Brass Hose Mender.....
EV BM6	3/4" Brass Hose Mender.....



STEEL (Zinc-Plated) HOSE MENDERS *

150 PSI • Hose Barb x Hose Barb

Part No.	Description
EV DMA	1/4" Steel Hose Mender.....
EV DMB	3/8" Steel Hose Mender.....
EV DM1	1/2" Steel Hose Mender.....
EV DM6	3/4" Steel Hose Mender.....
EV DM11	1" Steel Hose Mender.....
EV DM16	1-1/4" Steel Hose Mender.....
EV DM21	1-1/2" Steel Hose Mender.....
EV DM26	2" Steel Hose Mender.....
EV DM36	3" Steel Hose Mender.....
EV DM46	4" Steel Hose Mender.....
EV DM66	6" Steel Hose Mender.....
EV DM86	8" Steel Hose Mender.....



304/316SS HOSE MENDERS *

150 PSI • Hose Barb x Hose Barb

Part No.	Size	S.S.	Net Ea.	Part No.	Size	S.S.
EV RM2	1/4"	316	\$ 5.10	EV SF150S	1-1/2"	304
EV RM3	3/8"	316	6.50	EV RDM21	1-1/2"	316
EV SF50S	1/2"	304	6.00	EV SF200S	2"	304
EV RM4	1/2"	316	10.30	EV RDM26	2"	316
EV SF75S	3/4"	304	4.75	EV SF300S	3"	304
EV RM6	3/4"	316	15.10	EV RDM36	3"	316
EV SF100S	1"	304	7.00	EV SF400S	4"	304
EV RDM11	1"	316	38.00	EV RDM46	4"	316
EV SF125S	1-1/4"	304	8.00	EV SF600S	6"	304
EV RDM16	1-1/4"	316	40.75			



* Not for compressible products such as air, nitrogen or steam. Working pressure may vary with the construction of the hose, clamping system and the application. Rubber Manufacturers Association (RMA) handbook outlines field testing procedures for hose menders which should be followed exactly.

King Nipples Steel & Stainless, MPT X HB

Part No.	MPT & Shank Dia.	Material **	Std. Pkg.
TF STN050	* 1/2"	Steel King	-
TF STN075	* 3/4"	Steel King	-
TF STN100	* 1"	Steel King	50
TF STN125	* 1-1/4"	Steel King	40
TF STN150	* 1-1/2"	Steel King	40
TF STN200	* 2"	Steel King	40
TF STN250	* 2-1/2"	Steel King	10
TF STN300	* 3"	Steel King	12
TF STN400	* 4"	Steel King	8
TF STN600	* 6"	Steel King	4
TF STN800	* 8"	Steel King	4
EV RST-1/4	1/4"	316 SS Hex	-
EV RST-3/8	3/8"	316 SS Hex	-
EV RST1	1/2"	316 SS Hex	-
TK HB075SS	3/4"	316 SS Hex	-
TK HB100SS	1"	316 SS Hex	-
TK HB125SS	1-1/4"	316 SS Hex	-
TK HB150SS	1-1/2"	304 SS Hex	-
TK HB200SS	2"	316 SS Hex	-
EV RST30	* 2-1/2"	316 SS King	-
TK HB300SS	* 3"	316 SS King	-
TK 316-A300	3"	316 S.S. Hex Nipple	-
EV RST40	4"	316 S.S. Hex Nipple	-
EV RST60	* 6"	316.S.S. King Nipple	-



King



Hex

Jump Sizes

EV RST-1/4X1/8	1/8"	MPT x 1/4"	HB 304S.S.	Hex
TK HB025/038SS	1/4"	MPT x 3/8"	HB 316 S.S.	Hex
TK HB025/050SS	1/4"	MPT x 1/2"	HB 316 S.S.	Hex
TK HB038/050SS	3/8"	MPT x 1/2"	HB 316 S.S.	Hex
TK HB050/038SS	1/2"	MPT x 3/8"	HB 316 S.S.	Hex
TK HB050/058SS	1/2"	MPT x 5/8"	HB 316 S.S.	Hex
TK HB050/075SS	1/2"	MPT x 3/4"	HB 316 S.S.	Hex
TK HB075/050SS	3/4"	MPT x 1/2"	HB 316 S.S.	Hex
TK HB075/100SS	3/4"	MPT x 1"	HB 316 S.S.	Hex
TK HB100/075SS	1"	MPT x 3/4"	HB 316 S.S.	Hex
EV RST1510	* 1"	MPT x 1-1/4"	HB 316 S.S.	King
EV RST2520	* 1-1/2"	MPT x 2"	HB 316 S.S.	King
EV RST2025	* 2"	MPT x 1-1/2"	HB 316 S.S.	King
EV RST3525	* 2"	MPT x 3"	HB 316 S.S.	King

* King Nipple Style - No Hex. ** 10% Quantity Discount on Std. Pkgs.

See "Steel Hose Fittings" on adjacent pages for smaller sizes