12-Volt Pressure Washer


12-Volt Pressure Washer featuring *Cat* plunger pump with built-in unloader and chemical injector. Designed to be easily mounted on your equipment frame and powered from your existing battery. Output is 1.50 GPM at 1000 PSI. Motor is 12-volt, 1 Hp, 80 full load amps. 25' Spray hose and trigger wand with 18" extension are standard. 3/8" Brass quick couplers to easily remove hose from pump are also included.



12-Volt Pressure Washer (Low Flow)

Compact washdown kits featuring standard *Pumptec* pumps. Simple, quiet and reliable. All kits include pump, 12Volt motor, adjustable pattern spray wand, unloader relief valve, inlet filter, inlet hose and on/off switch, (except **80729**). All models can be easily mounted to your equipment frame.

80398 is rated to 1.0 GPM and 200 PSI. Also includes 25ft spray hose and wire harness. 81860 is rated to 1.3 GPM and 600 PSI. With switch, no discharge hose or wire harness. 80729 is rated to 1.4 GPM and 700 PSI. No discharge hose or switch, for direct wiring. 70488 is an adjustable pattern spray wand that comes with all models.



12-Volt Pressure Washer Unit (High Flow)

Pumptec 12-Volt Wash Down Units featuring the X Series pump with ceramic plungers. Fill and wash down in one unit. Two models to choose from. Both include pump, motor, inlet plumbing kit, 25' discharge hose and adjustable spray wand. (Also available in 120 or 240 volt if required).

PU	MP ₁ =		
Part No.	Flow	<u>PSI</u>	W
PX 81561	5.0	100	20 II
PX 81651	6.4	160	20 II



Hydraulic Pressure Washer



This Hydraulically-Driven Pressure Washer is designed for remote and explosion-proof environments where electricity cannot be used. The ideal choice for use with washdown and cleaning of construction equipment, agricultural equipment, concrete cleanup, etc.



Kit is complete with hydraulic motor, *AR* plunger pump, mounting rails, unloader valve, chemical injector pressure gauge, and quick disconnect for hose. Models come with spray wand and 50' hose as shown. A wide variety of flows and pressures are available to meet your needs. Ports are 1/2" FPT x 3/4" FGHT inlet and 3/8" female quick disconnect outlet. Rated to 140° F.

	Hydraulic Motor		
Part No.	Cleaning Capacity	Requirements	Wt.
AR HYDRK1520-1000	3.0 GPM @ 1000 PSI	5.6 GPM @ 900 PSI	41 lbs.
AR HYDRK1520-1500	4.0 GPM @ 1500 PSI	7.5 GPM @ 1300 PSI	41 lbs.
AR HYDRK1520-2000	4.0 GPM @ 2000 PSI	7.5 GPM @ 1800 PSI	45 lbs.

Complete Water Jetters with Reel and Hose


Complete and Ready-To-Use Water Jetters designed to blast through sludge, soap and grease blockages. Simply guide the hose and nozzle into the drain, water thrust propels it down the line and through buildups.

Features: Plunger pumps • Heavy-duty, 2-wheel frames with pneumatic tires • Jetter valve • Pressure unloader valve • Pressure gauge • Hose reel • Jetter hose • Jetter nozzle.

210J features 2.3 HP / Single phase / 115 Volt electric motor and comes with 50' of 1/4" hose.

440J features *Honda* gas engine with recoil start and come with 100' of 1/4" hose.

- Both Models Ship Free Freight -



Viton® is a registered trademark of DuPont Performance Elastomers