

(LP or Natural Gas)

Stationary Natural Gas or LP Fired Pressure Washers are engineered to provide maximum cleaning efficiency. Strong enough to tackle the most demanding cleaning jobs. Designed to provide water temperatures to 180° F. All units feature chemical solution system for injecting cleaning chemicals into the pumping line. All units feature *General* Plunger Pumps driven by electric motors.

Standard Features Include: Trigger spray gun with wand • 50' high pressure hose with quick couplers • Unloader valve • Safety pop-off valve • Flow switch for burner shutdown • Schedule 80 1/2" Coil • Adjustable Thermostat • Upstream high pressure chemical injection system • Low water shut-off • Draft diverters available as an option. Gas valves are 1". **Note: All units are fired and tested. (Please specify LP or Natural Gas). 5 Year prorated coils. Made in USA.**



Part No.	Flow	PSI	HP	Wt.
DU DS3-2400	3 GPM	2400	5 HP / 1 PH	725 lbs.
DU DS3-2400/3	3 GPM	2400	5 HP / 3 PH	725 lbs.
DU DS4-3000	4 GPM	3000	8 HP / 1 PH	800 lbs.
DU DS4-3000/3	4 GPM	3000	8 HP / 3 PH	800 lbs.
DU DS5-3000	5 GPM	3000	10 HP / 3 PH	860 lbs.
DU DS7-3000	7 GPM	3000	15 HP / 3 PH	1390 lbs.
DU DS10-2000	10 GPM	2000	15 HP / 3 PH	1640 lbs.
DU DS10-3000	10 GPM	3000	20 HP / 3 PH	1660 lbs.
DU Z01-00100	10" Draft Diverter as Add On for 3 GPM Units...			
DU Z01-00101	12" Std. Draft Diverter as Add On for 4-10 GPM Units			
DU Z01-00105	10" Motorized Draft Diverter, 3 GPM Units.....			
DU Z01-00104	12" Motorized Draft Diverter, 4-10 GPM Units....			
DU 12EIG	Electronic Ignition as Add On			
DU 12AUTO	Automatic Stop/Start Control -			



Provides Maximum Cleaning Efficiency!

50 ft. Hose

EASY-KLEEN
PRESSURE SYSTEMS LTD.



NEMA4 Control Panel

50 ft. Hose

Easy to Use, Easy to Maintain, Easy to Service, Efficient to Run and Safe

Buffalo Series Standard Features: General plunger pumps • Trigger spray gun with wand and nozzles • 50' of high pressure hose • Pressure relief valve • High pressure chemical injection • Water float tank • Quick Clean burners • Adjustable air flow vents • Auto On/Off with delay • 11 Gauge welded steel frame with powder coat finish • Adjustable thermostat • Schedule 80 or Schedule 160 coils sealed in ceramic blanket and stainless housing • TEFC 1 Phase or 3 Phase motors • Natural Gas or Propane, (Specify) • Belt drive pumps all units but EZ2435E1 and EZ3035E1 which are * Direct Drive • Made in Canada, ships from U.S.



Part No.	Description
EZ 2435E1	* 3.5 GPM @ 2400 PSI. 5 Hp/1 Phase/220V. Rated to 290,000 BTU. 46" L x 32" W x 46" H. Wt. 400 lbs.
EZ 3035E1	* 3.5 GPM @ 3000 PSI. 7.5 Hp/1 Phase/220V. Rated to 290,000 BTU. 46" L x 32" W x 46" H. Wt. 415 lbs.
EZ 20041	4.0 GPM @ 2000 PSI. 5.0 Hp/1 Phase/220V. Rated to 390,000 BTU. 55" L x 30" W x 48" H. Wt. 800
EZ 20043	4.0 GPM @ 2000 PSI. 5.0 Hp/3 Phase/220V/440V. Rated to 390,000 BTU. 55" L x 30" W x 48" H. Wt. 800.....
EZ 30041	4.0 GPM @ 3000 PSI. 7.5 Hp/1 Phase/220V. Rated to 390,000 BTU. 55" L x 30" W x 48" H. Wt. 800 lbs.
EZ 30043	4.0 GPM @ 3000 PSI. 7.5 Hp/3 Phase/208V/440V/575V. Rated to 390,000 BTU. 55" L x 30" W x 48" H. Wt. 800 lbs.
EZ 40043	4.0 GPM @ 4000 PSI. 10 Hp/3 Phase/208V/440V/575V. Rated to 390,000 BTU. 55" L x 35" W x 48" H. Wt. 1100 lbs.
EZ 60043	4.0 GPM @ 6000 PSI. 20 Hp/3 Phase/208V/440V/575V. Rated to 390,000 BTU. 68" L x 32" W x 51" H. Wt. 1300 lbs.
EZ 30051	5.0 GPM @ 3000 PSI. 10 Hp/1 Phase/208V. Rated to 390,000 BTU. 68" L x 32" W x 51" H. Wt. 1300 lbs.
EZ 30053	5.0 GPM @ 3000 PSI. 10 Hp/3 Phase/208V/440/575V. Rated to 390,000 BTU. 68" L x 32" W x 51" H. Wt. 1300 lbs.
EZ 36083	8.0 GPM @ 3600 PSI. 20 Hp/3 Phase/208V/440/575V. Rated to 720,000 BTU. 68" L x 32" W x 51" H. Wt. 1450 lbs.
EZ PRO-DH8	8" Draft Diverter for 290,000 to 390,000 BTU's.
EZ PRO-DH10	10" Draft Diverter for 510,000 to 720,000 BTU's.

* Direct Drive Pump/Motors.