

Ideal Systems for chemical foam washdown and/or sanitation. For use in agriculture, food and beverage, vehicle cleaning and industrial applications. Available in permanent wall mount systems, portable hand carry or portable cart units. All foamers are designed to combine air pressure, water and chemical mixture to create the type of clinging foam that is required for most cleaning/sanitation situations. Natural tanks allow for product level viewing.

All systems are complete and include needle valve for foam control, discharge hose, foam wands and necessary fittings. *(Inlet air and water hoses are not included)*. Rated to 100° F.

Wall Mount Foamer Unit

900WC Wall Mount Foamer Unit. Includes: Air driven chemical pump • Air pressure regulator • 50' of foam hose • Foaming nozzle • Chemical tube • Gasketed control enclosure. • Santoprene seal *(Viton® available)*.

Requires 5-10 cfm of air at 40-80 PSI. Creates up to 30 gallons of foam per minute and throws foam to a distance of 25'. Mix ratio of 14:1 to 320:1.

Part No.	Wt.
DE 900WC Wall Mount Foam Unit	31 lbs.



900WC

Hand Pump Up Foamer - 2 Gallon -

900-2PU Hand Pump Up Foamer. Easy, hand carry foamer for ease-of-use and portability. Includes: 2 Gallon tank • 3-1/2' of Hose • Trigger foam wand • Viton® seal.

Simply fill the tank with chemical water solution and pump up to pressurize. Adjustable needle valve controls foam consistency. Produces approximately 1/2 gallon of foam per minute.

Part No.	Wt.
DE 900-2PU Pump Up Foam Unit	6 lbs.



900-2PU

Portable Foamer - 10 Gallon -

910 Portable Foamer Unit. Wheeled cart with 10 gallon solution tank feeds the air-driven chemical pump. Includes: Air pressure regulator • 20' of foam hose • Foam nozzle assembly • Air pump • Tank assembly • Viton® seal.

Requires 5-8 cfm of air at 40-80 PSI. Throws foam to a distance of 15'-20'. Produces approximately 15-30 gallons of foam per minute.

Part No.	Wt.
DE 910 10 Gallon Portable Foam Unit	39 lbs.



910

Portable Foamer - 25 Gallon -

925 Portable Foamer Unit. Wheeled cart with 25 gallon solution tank feeds the air-driven chemical pump. Includes: Air pressure regulator • 30' of foam hose • Foam nozzle assembly • Air pump • Tank assembly • Viton® seal.

Requires 5-10 cfm of air at 40-80 PSI. Throws foam to a distance of 25'-35'. Produces approximately 20-45 gallons of foam per minute.

Part No.	Wt.
DE 925 25 Gallon Portable Foam Unit	50 lbs.



925

Viton® is a registered trademark of DuPont Performance Elastomers