

## Series 2410 UHMWPE Chemical Hose

**Applications:** This clear high molecular weight (UHMW) polyethylene tube will handle 98% of the most common chemical without leaching and contaminating the product being conveyed. Refer to the chemical guide to determine compatibility with chemicals and applications. Rated to 200 PSI.



**Tube:** Opaque ultra-high molecular weight polyethylene  
**Cover:** Corrugated Blue EPDM  
**Reinforcement:** Multiple textile plies with dual wire helix.

**Temp Rating:**  
 -40° F to 212° F

Specified length is overall assembly length.


Part No.	I.D.	O.D.	Bend	Working Pressure	Wt./ (Lbs./Ft.)	Std. Pkg. of 100' Discount
GP 2410-3/4	3/4"	1.22"	3.5	200 PSI	.42	-
GP 2410-1	1"	1.46"	4.0	200 PSI	.48	25%
GP 2410-1-1/4	1-1/4"	1.77"	4.0	200 PSI	.71	25%
GP 2410-1-1/2	1-1/2"	2.01"	5.0	200 PSI	.81	25%
GP 2410-2	2"	2.56"	6.0	200 PSI	1.17	25%
GP 2410-3	3"	3.62"	9.0	150 PSI	2.01	25%

GP 2410-2X20 2" X 20' Hose Assembly with 316SS Male x Female Ends.....

**Other Assemblies Available!**

## Series 2425 X-Link Chemical Hose

**Applications:** Cross-link chemical hose solves most chemical handling problems. The tube compound is resistant to 90% of chemicals, solvents and petroleum products used in industry. The heavy wall resists kinking and crushing for extra safety. Refer to the chemical guide to determine compatibility with chemicals and applications. Rated to 150 PSI. Specified length is overall assembly length. **Cut lengths in 5' increments.**



**Tube:** Cross-linked polyethylene  
**Cover:** Smooth Green EPDM  
**Reinforcement:** Multiple textile plies with dual wire helix.

**Temp Rating:**  
 -25° F to 150° F

Specified length is overall assembly length.

Part No.	I.D.	O.D.	Bend	Working Pressure	Wt./ (Lbs./Ft.)	Std. Pkg. of 100' Discount
GP 2425-3/4	3/4"	1.26"	4.0	200 PSI	.50	-
GP 2425-1	1"	1.50"	5.0	200 PSI	.55	25%
GP 2425-1-1/4	1-1/4"	1.77"	6.5	200 PSI	.75	25%
GP 2425-1-1/2	1-1/2"	2.01"	8.0	200 PSI	.89	25%
GP 2425-2	2"	2.56"	10.0	150 PSI	1.18	25%

GP 2425-2X20 2" X 20' Hose Assembly with 316SS Male x Female Ends.....

**Other Assemblies Available!**

## BESTWAY SHIPPING

"BestWay" shipping may not be the quickest option, but it will help to lower your freight bill. If you select this method of shipping, Dultmeier will calculate the cheapest way to ship your package(s) at the time of shipment.



Please remember there are No Returns on customer specified cut lengths of hose.

## Series 2450 Teflon Lined Chemical Hose



**Applications:** Recommended for the transfer of products that require a hose tube with the highest level of chemical resistance.

The smooth bore design is ideal for the unrestricted transfer of fluids and promotes draining and cleaning. The hose is reinforced with multiple plies of polyester yarn with dual wire helix. This reinforcing combination provides full vacuum capabilities, kink resistance and high working pressure ratings. Other cover colors are available (red, black, gray, yellow, green and white). Meets or exceeds the requirements of FDA and USDA under 21 CFR 177, 1550, 3-A sanitary standards 10-15.

**Tube:** Teflon® (FEP) backed with modified XLPE

**Temp Rating:**  
 -40° F to 300° F

**Cover:** Blue EPDM

**Other Assemblies Available!**

**Reinforcement:** Multiple textile plies with dual wire helix

Specified length is overall assembly length.

Part No.	I.D.	O.D.	Bend	Working Pressure	Wt./ (Lbs./Ft.)
GP 2450-3/4	3/4"	1.29"	4.0	200 PSI	.52
GP 2450-1	1"	1.56"	5.0	200 PSI	.63
GP 2450-1-1/2	1-1/2"	2.05"	8.0	200 PSI	.93
GP 2450-2	2"	2.55"	9.0	200 PSI	1.14
GP 2450-3	3"	3.59"	18.0	150 PSI	1.77

GP 2450-2X20 2" X 20' Hose Assembly with 316SS Male x Female Ends

Only Sold in 100' Reels



## Acid Chemical Hose



"Mustang"

**45HW** handles 99% of all chemicals. Sulfuric Acid to 90% on intermittent transfer service only. **Recommended For:** Suction and discharge requiring a wide range of chemicals. Ask for Detailed List. **Temperature Range:** -40° to +250° F. **Tube:** Cross-linked Polyethylene. **Reinforcement:** 2-Ply synthetic fiber with a spiral wire. **Cover:** EPDM black with an orange and white stripe. Use permanent couplings above 125° F.

**Not Suitable for DEF**

Part No.	I.D.	O.D.	PSI	Wt./ Ft.	100' Std. Pkg. Pkg. Disc.
GA 45HW-1	1"	1.50"	200	.54	25%
GA 45HW-1-1/4	1-1/4"	1.75"	200	.64	-
GA 45HW-1-1/2	1-1/2"	2.04"	200	.84	25%
GA 45HW-2	2"	2.54"	200	1.60	25%
GA 45HW-3	3"	3.58"	150	2.25	25%

**Order from our entire inventory online!**

- Current Pricing
- Web Specials
- Closeout Items
- Current Flyers
- Order Status
- Parts Schematics

Scan our QR Code

www.dultmeier.com